



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Feed-Through**
Modular Terminal Block Product Type: **Screw Clamp Terminal Block**
Primary Product Color: **Blue**
Product Spacing: **16 mm [.629 in]**
Number of Positions: **2**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Gauge Type	B9
Number of Levels	1
Number of Poles	2
Number of Circuits	1
Block Function	Feed-Through
Number of Positions	2

Electrical Characteristics

Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	600 V
Impulse Withstanding Voltage Rating (IEC)	8000 V
Voltage Rating (CSA)	600 V
Current Rating (CSA)	150 A
Dielectric Withstanding Voltage (Max)	3500 V
Short-Time Withstanding Current Rating @ 1s	4200 A
Voltage Rating (IEC)	1000 V
Current Rating (UL)	150 A



Current Rating (IEC)	125 A
----------------------	-------

Operating Voltage	1000 VAC
-------------------	----------

Body Features

Product Weight	50 g
----------------	------

Primary Product Color	Blue
-----------------------	------

Termination Features

Termination Method to Wire & Cable	Screw Terminal
------------------------------------	----------------

Mechanical Attachment

DIN Rail Mounting Type	G32, TH35-15, TH35-7.5
------------------------	------------------------

Tightening Torque	24.9 in-lbs
-------------------	-------------

Connector Mounting Type	DIN Rail
-------------------------	----------

Housing Features

Housing Material	Polyamide 6.6
------------------	---------------

Dimensions

Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	10 – 0 AWG
--	------------

Wire Stripping Length	17 mm[.669 in]
-----------------------	----------------

Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	6 – 35 mm ²
---	------------------------

Product Depth	46.5 mm
---------------	---------

Product Width	16 mm[.629 in]
---------------	----------------

Product Length	46.5 mm
----------------	---------

Product Height	49 mm
----------------	-------

Product Spacing	16 mm[.629 in]
-----------------	----------------

Wire Size	35 mm ²
-----------	--------------------

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
--------------------------------	-------------------------

Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

IP Rating	IP20
-----------	------

UL Flammability Rating	UL 94V-0
------------------------	----------



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts




TE Part # 1SNK916303R0000
JB16-3



TE Part # 1SNA103588R2600
SCFT1









TE Part # 1SNA103775R0000
RC65-BL




TE Part # 1SNA103776R0100
RC65-RD



 TE Part # 1SNA206230R1100 RC610-GN	 TE Part # 1SNA206231R0600 RC610-YL	 TE Part # 1SNA206232R0700 RC610-OR	 TE Part # 1SNA206235R0200 RC610-RD
 TE Part # 1SNA232000R0000 RC65	 TE Part # 1SNA233000R0100 RC610	 TE Part # 1SNA234000R0200 RC810	 TE Part # 1SNA238000R1600 RC1010
 TE Part # 1SNK916302R0000 JB16-2	 TE Part # 1SNK916304R0000 JB16-4	 TE Part # 1SNK916305R0000 JB16-5	 TE Part # 1SNK916310R0000 JB16-10
 TE Part # 1SNA007865R2600 FC2	 TE Part # 1SNA116795R1100 SCFCV1-2	 TE Part # 1SNA167860R0100 FC4	 TE Part # 1SNA176816R1200 CPV1-2

Also in the Series | ENTRELEC SNA


 Modular Terminal Blocks(181)	 Terminal Block & Strip Conducting Accessories(25)	 Terminal Block & Strip Insulating Accessories(14)
---	---	--

Customers Also Bought

1SNA125124R0100

Feed-Through, Screw Clamp Terminal Block, Blue, Product Spacing 16 mm [.629 in], 2 Position, Screw Terminal, ENTRELEC SNA, Modular Terminal Blocks






TE Part #163083-8
[.062 DIA SOC.ASS.3+](#)



TE Part #1SNA165111R1400
[M35/16.P](#)



TE Part #1SNA165130R2300
[M16/12.P](#)



TE Part #1SNA234000R0200
[RC810](#)



TE Part #1SNK508020R0000
[ZS10-BL](#)



TE Part #1SNK516020R0000
[ZS35-BL](#)

TE Part #1SNA173217R2600
[BJM62](#)



TE Part #T1902240232-100
[H24BPR-TS/GHC-2M32](#)



TE Part #T3100000011-000
[5XECD.772.001](#)



TE Part #4-1106053-3
[O-Ring 98x3](#)

Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1SNA125124R0100_E.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNA125124R0100_E.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNA125124R0100_E.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[Catalogue - ENTRELEC terminal-blocks-sna-series](#)

English

[M35/16.N](#)

English

1SNA125124R0100

Feed-Through, Screw Clamp Terminal Block, Blue, Product Spacing 16 mm [.629 in], 2
Position, Screw Terminal, ENTRELEC SNA, Modular Terminal Blocks



ENTRELEC Terminal Blocks Catalogue (RUS)