

Han-Modular coax F-contact 500hm (RG174)



	Part number	09 14 000 6211
	Specification	Han-Modular coax F-contact 50Ohm (RG174)
	HARTING eCatalogue	https://b2b.harting.com/09140006211

Image is for illustration purposes only. Please refer to product description.

Identification

China RoHS

REACH Annex XVII substances

Category	Contacts		
Series	DIN 41626		
Type of contact	Coaxial contact		
Description of the contact	for cables RG 174 U, 188 AU, 316 U		
Version			
Termination method	Solder/crimp termination		
Gender	Male		
Manufacturing process	Turned contacts		
Technical characteristics			
Operating current	≤1.5 A		
Contact resistance	≤10 mΩ		
Impedance	50 Ω		
Material properties			
Material (contacts)	Copper alloy		
Surface (contacts)	Gold plated		
RoHS	compliant with exemption		
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight		
ELV status	compliant with exemption		

Page 1 / 2 | Creation date 2020-02-04 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

50

No



Material properties

REACH ANNEX XIV substances	No		
REACH SVHC substances	Yes		
REACH SVHC substances	Lead		
Specifications and approvals			
Specifications	EN 60664-1 IEC 61984		
Commercial data			
Packaging size	10		
Net weight	2.16 g		
Country of origin	Germany		
European customs tariff number	85366910		
eCl@ss	27440204 Contact for industrial connectors		