

DOP Document Number : ECCE-03-21

Standard & product range.

R2V XP C 32-321 Circular Conductor

No. of Cores	Size
1	1.5 mm ² to 630 mm ²
2	1.5 mm ² to 35 mm ²
3, 4	1.5 mm ² to 300 mm ²
5	1.5 mm ² to 95 mm ²
7, 12, 19, 24, 27, 37	1.5 mm ² to 2.5 mm ²

Traceability of each cable is followed by drum numbers

Intended Use of Product Type

Supply of electricity in buildings and other civil engineering
Works with the objective of limiting the generation and spread of fire and smoke

Manufacturer Information

Manufacturer : -EL SEWEDY CABLES-
Office: plot 27, 1st district.5th settlement, new Cairo.
Tel: 72599732-27599733-27599734
Fax: 27599735 P.O.Box:311-post code: 11853
Factory Address WWW.ELSEWEDY.COM
Factory: 10th of Ramadan City Zone, A 3,
Tel.: (2015) 411350 **fax:** (2015)411366
PO.Box: 1748 post code: 10505

System or Systems of Assessment and Verification of Constancy of Performance

System 3

Notified Body/laboratory

IMO No. 0051

Performances Declared

Essential Characteristic	Performance	Harmonized Technical Specification
<i>Reaction to Fire</i>	Eca	
<i>Smoke Production</i>	-	
<i>Flaming Droplets</i>	-	EN 50575:2014+A1:2016
<i>Acidity</i>	-	
<i>Dangerous substance</i>	None	

This declaration of performance is issued under the responsibility of the identified manufacturer.


Eng. Ayman Elkholy
Technical Director