



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Fuse**

Modular Terminal Block Product Type: **Screw Clamp Terminal Block**

Primary Product Color: **Gray**

Product Spacing: **8 mm [.314 in]**

Number of Positions: **2**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Gauge Type	A4
Number of Levels	2
Number of Poles	4
Number of Circuits	2
Block Function	Fuse
Number of Positions	2

Electrical Characteristics

Impulse Withstanding Voltage Rating (IEC)	6000 V
Voltage Rating (IEC)	500 V
Current Rating (IEC)	6.3 A
Operating Voltage	500 VAC

Body Features



Product Weight	30 g
----------------	------

Primary Product Color	Gray
-----------------------	------

Termination Features

Termination Method to Wire & Cable	Screw Terminal
------------------------------------	----------------

Mechanical Attachment

Tightening Torque	4.4 in-lbs
-------------------	------------

DIN Rail Mounting Type	G32, TH35-15, TH35-7.5
------------------------	------------------------

Terminal Block Disconnect Type	Lever
--------------------------------	-------

Connector Mounting Type	DIN Rail
-------------------------	----------

Housing Features

Housing Material	Polyamide 6.6
------------------	---------------

Dimensions

Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	.5 – 6 mm²
--	------------

Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.5 – 4 mm²
---	------------

Wire Stripping Length	9.5 mm[.374 in]
-----------------------	-----------------

Tool Size	4 mm[.157 in]
-----------	---------------

Product Depth	41 mm
---------------	-------

Product Width	8 mm[.314 in]
---------------	---------------

Product Length	41 mm
----------------	-------

Product Height	56.5 mm
----------------	---------

Product Spacing	8 mm[.314 in]
-----------------	---------------

Wire Size	4 mm²
-----------	-------

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
--------------------------------	-------------------------

Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

IP Rating	IP20
-----------	------

UL Flammability Rating	UL 94V-0
------------------------	----------



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts




TE Part # 1SNA173523R1100
PC81-10



TE Part # 1SNA206230R1100
RC610-GN








TE Part # 1SNA206231R0600
RC610-YL




TE Part # 1SNA206232R0700
RC610-OR



 TE Part # 1SNA206235R0200 RC610-RD	 TE Part # 1SNA233000R0100 RC610	 TE Part # 1SNA234000R0200 RC810	 TE Part # 1SNA007865R2600 FC2
 TE Part # 1SNA008288R1500 FU520	 TE Part # 1SNA008290R1300 FU520	 TE Part # 1SNA008291R0000 FU520	 TE Part # 1SNA008292R0100 FU520
 TE Part # 1SNA114205R2000 AD2.5	 TE Part # 1SNA116900R2700 BADH	 TE Part # 1SNA116913R0700 FEM8D2S	 TE Part # 1SNA163043R2100 AL2
 TE Part # 1SNA163261R0000 AL3	 TE Part # 1SNA167860R0100 FC4	 TE Part # 1SNA168672R1100 TGA8	 TE Part # 1SNA168673R1200 TGA8

Also in the Series | ENTRELEC SNA

 Modular Terminal Blocks(181)	 Terminal Block & Strip Conducting Accessories(25)	 Terminal Block & Strip Insulating Accessories(14)
---	---	--

Customers Also Bought

1SNA115936R0500

Fuse, Screw Clamp Terminal Block, Gray, Product Spacing 8 mm [.314 in], 2 Position, Screw Terminal, Signal, ENTRELEC SNA, Modular Terminal Blocks



TE Part #1SNA115646R2200
[M4/8.D2.SFL](#)

TE Part #1SNA115659R0700
[M4/8.SN](#)

TE Part #1SNA116771R2000
[FED3E](#)

TE Part #1SNA173220R0500
[PR30](#)

TE Part #1SNA173523R1100
[PC81-10](#)

TE Part #1SNA008290R1300
[FU520](#)

TE Part #1SNA116913R0700
[FEM8D2S](#)

TE Part #1SNA168974R0000
[BJM8 10 poles](#)

TE Part #1SNA178033R2600
[BJD6](#)

TE Part #1SNA179672R1400
[BJM6D-10](#)

Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1SNA115936R0500_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNA115936R0500_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNA115936R0500_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[Catalogue - ENTRELEC terminal-blocks-sna-series](#)

English

[M4/8.D2.SFD3](#)

English



ENTRELEC Terminal Blocks Catalogue (RUS)

Agency Approvals

CE Declaration of Conformity

English