

ACCESSOIRES POUR RACCORDS EN ACIER GALVANISÉ



Viroles de continuité de masse, en acier galvanisé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
A	B	C	D	E						
-	3/8"	10,4	-	-	-	-	-	50	297.212.0	1,3
-	1/2"	13,7	-	-	-	-	-	25	297.216.0	1,3
-	3/4"	18,8	-	-	-	-	-	25	297.220.0	1,4
-	1"	24,2	-	-	-	-	-	25	297.226.0	1,8
-	1.1/4"	31,6	-	-	-	-	-	5	297.235.0	2
-	1.1/2"	36,8	-	-	-	-	-	5	297.240.0	2,4
-	2"	48	-	-	-	-	-	5	297.250.0	2,8
-	2.1/2"	58,5	-	-	-	-	-	5	297.263.0	6,4
-	3"	72	-	-	-	-	-	5	297.275.0	7,2
-	4"	95	-	-	-	-	-	1	297.299.0	7,6

* A partir du diamètre 1.1/4", la virole est en aluminium



Contre-écrous NPT "Tiger Grip", en acier galvanisé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
A	B	C	D	E						
NPT 1/2"	-	-	-	-	-	-	-	100	297.416.0	0,5
NPT 3/4"	-	-	-	-	-	-	-	100	297.420.0	0,8
NPT 1"	-	-	-	-	-	-	-	50	297.426.0	1,3
NPT 1.1/4"	-	-	-	-	-	-	-	50	297.435.0	1,8
NPT 1.1/2"	-	-	-	-	-	-	-	50	297.440.0	2,2
NPT 2"	-	-	-	-	-	-	-	25	297.450.0	2,8
NPT 2.1/2"	-	-	-	-	-	-	-	1	297.463.0	3,5
NPT 3"	-	-	-	-	-	-	-	1	297.475.0	5,6
NPT 4"	-	-	-	-	-	-	-	1	297.499.0	9,8



Bague en néoprène NPT, avec face arrière en acier galvanisé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
A	B	C	D	E						
NPT 1/2"	-	-	-	-	-	-	-	100	297.016.0	0,5
NPT 3/4"	-	-	-	-	-	-	-	100	297.020.0	0,5
NPT 1"	-	-	-	-	-	-	-	50	297.026.0	0,6
NPT 1.1/4"	-	-	-	-	-	-	-	50	297.035.0	0,8
NPT 1.1/2"	-	-	-	-	-	-	-	50	297.040.0	1,4
NPT 2"	-	-	-	-	-	-	-	50	297.050.0	1,4


ACCESSOIRES POUR RACCORDS EN ACIER GALVANISÉ



Ecrou de raccord avec œillet de mise à la terre externe, en acier galvanisé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
-	3/8"	-	-	-	26	-	-	25	297.512.0	2,8
-	1/2"	-	-	-	29	-	-	25	297.516.0	3,4
-	3/4"	-	-	-	35	-	-	10	297.520.0	-
-	1"	-	-	-	42	-	-	5	297.526.0	-
-	1.1/4"	-	-	-	56	-	-	5	297.535.0	-
-	1.1/2"	-	-	-	64	-	-	1	297.540.0	-
-	2"	-	-	-	77	-	-	1	297.550.0	-



Ecrou de raccord avec treillis métallique pour décharge de traction, en acier galvanisé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
-	3/8"	-	-	-	26	-	-	20	297.312.0	2,5
-	1/2"	-	-	-	29	-	-	20	297.316.0	5
-	3/4"	-	-	-	35	-	-	20	297.320.0	7,5
-	1"	-	-	-	42	-	-	20	297.326.0	8,5
-	1.1/4"	-	-	-	56	-	-	10	297.335.0	10
-	1.1/2"	-	-	-	64	-	-	10	297.340.0	12
-	2"	-	-	-	77	-	-	5	297.350.0	14

Raccords
spéciaux