

PRODUCT-DETAILS

F204 AC-40/0.03-L

F204 AC-40/0.03-L Residual Current Circuit Breaker 4P AC type 30 mA



Informations générales

Extension du type de produit	F204 AC-40/0.03-L
Code de produit	2CSF204023R1400
EAN	8012542816003
Description courte	F204 AC-40/0.03-L Residual Current Circuit Breaker 4P AC type 30 mA
Description longue	The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product is suitable for installations where neutral on the left is .

ABB EcoSolutions

ABB EcoSolutions	Oui
------------------	-----

Valeur Circulaire

Principes du Design Circulaire - Taux de Recyclabilité	Concu pour utiliser des ressources recyclables et réutilisables - Norme EN45555 - 52,5 %
--	--

Déchets destinés à l'enfouissement en décharge - Destination	Aucun déchet non-dangereux mis en décharge -
Matériau Durable constitutif des Emballages	Papier recyclé - 78 %
Amélioration de l'efficacité des ressources pour les clients	Efficacité numérique - Le produit bénéficie d'un support numérique afin d'optimiser son utilisation et, à terme, optimiser les biens et services du client -
Proposé avec une durée de vie prolongée	Durabilité du produit
Proposition de reprise	Reprendre pour recycler
Instructions relatives à la fin de vie	9AKK108468A4361

Eco Transparence

Environmental Product Declaration - EPD	9AKK108467A3700
---	-----------------

Technique

Normes et standards	IEC/EN 61008
Type of Residual Current	AC type
Tension nominale (U_r)	230/400 V
Tension	230 / 400 V AC
Tension assignée d'isolement (U_i)	500 V
Tension assignée de tenue aux chocs (U_{imp})	4 kV
Courant nominal (I_n)	40 A
Rated Residual Current	30 mA
Rated Conditional Short-Circuit Current (I_{nc})	10 kA
Pouvoir assigné de coupure de service en court-circuit (I_{cs})	1 kA
Maximum Surge Current	0.25 kA
Leakage Current Type	AC
Fréquence assignée (f)	50 ... 60 Hz
Power Loss	at Rated Operating Conditions per Pole 3.2 W
Power Supply Connection	Arbitrary
Electrical Endurance	10000 cycle
Nombre de pôles	4
Operating Characteristic	Instantaneous
Position of Neutral Terminals	Left
Type de montage	DIN-Rail
Options Provided	None

Accessories Available	Oui
Connecting Capacity	Busbar 10 mm ² Rigid 25 ... 25 mm ² Flexible 25 ... 25 mm ²
Section nominale	4 - Multi-Wired 0...25 mm ² 1 - Solid-Core 25...25 mm ²

Material Compliance

Informations RoHS	9AKK106713A5602
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Date RoHS	20211115
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environnement

Température extérieure	-25...55 °C
Température de l'air ambiant	Operation -25...55 °C
Indice de protection	IP2X
Degré de pollution	2
Resistance to Vibrations	20 Cycles with Load 0.8 In: 1g or 1mm 50 ... 150 ... 5 Hz
Résistance aux chocs selon CEI 60068-2-27	25g 2 shocks 13 ms
Informations environnementales	Refer to RoHS

Technique UL/CSA

Short-Circuit Current Rating (SCCR)	30 mA
--	-------

Dimensions

Width in Number of Modular Spacings	4
Produit Largeur Net	0.070 m
Produit Hauteur Net	0.085 m
Produit Longueur Net	0.069 m
Poids net	0.360 kg
Profondeur d'encastrement (t ₂)	69 mm

Commande

Emballage Niveau 1	box 1 pièce
Unités	
Emballage Niveau 1 Poids	0.415 kg

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité	9AKK106713A5602
- CE	

Installation

Instructions et manuels	9AKK107991A6127
-------------------------	-----------------

Downloads Préférés

Fiche produit, informations techniques	9AKK107991A8329
--	-----------------

Classifications

ETIM 8	EC000003 - Residual current circuit breaker (RCCB)
ETIM 9	EC000003 - Residual current circuit breaker (RCCB)
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363030
eClass	V11.0 : 27142201
Code de classification d'objet	F

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200912R0001	S2C-H6R Auxiliary Contact	S2C-H6R	2	piece
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	2	piece
2CDS200946R0001	S2C-H6-11R Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0003	S2C-H6-02R Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200946R0002	S2C-H6-20R Auxiliary Contact	S2C-H6-20R	1	piece
2CSS200933R0011	F2C-A1 Shunt trip	F2C-A1	1	piece
2CSS200933R0012	F2C-A2 Shunt trip	F2C-A2	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage Release	S2C-UA 230 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC Undervoltage Release	S2C-UA 24 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage Release	S2C-UA 24 AC	1	piece
2CSS200911R0008	S2C-UA 48 DC Undervoltage Release	S2C-UA 48 DC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage Release	S2C-UA 110 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC Undervoltage Release	S2C-UA 400 AC	1	piece
2CSS200911R0001	S2C-UA 12 DC Undervoltage Release	S2C-UA 12 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC Undervoltage Release	S2C-UA 230 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC Undervoltage Release	S2C-UA 110 DC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage Release	S2C-UA 48 AC	1	piece
2CSS200910R0005	S2C-OVP1 Overvoltage Release	S2C-OVP1	1	piece
2CSS200993R0005	S2C-OVP2 Overvoltage Release	S2C-OVP2	1	piece
2CSF200997R0013	F2C-CM Motor operating device	F2C-CM	1	piece
2CSF200996R0013	F2C-ARI Auto-reclosing unit	F2C-ARI	1	piece

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Protection différentielle → Interrupteurs différentiels



ABB
Eco
Solutions™