

ACCESSOIRES POUR RACCORDS EN LAITON NICKELÉ



Viroles de continuité de masse rebord évasé, en acier galvanisé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
A	B	C	D	E						
-	3/8"	11	-	-	-	-	-	50	815.011.2	0,4
-	1/2"	14,5	-	-	-	-	-	50	815.016.2	0,5
-	3/4"	19,4	-	-	-	-	-	25	815.021.2	0,7
-	1"	24,7	-	-	-	-	-	25	815.029.2	1,1
-	1.1/4"	33,3	-	-	-	-	-	10	815.036.2	1,5
-	1.1/2"	38	-	-	-	-	-	10	815.042.2	2,1
-	2"	49	-	-	-	-	-	10	815.048.2	3,2
-	2.1/2"	60,7	-	-	-	-	-	5	815.063.2	4,3
-	3"	75,5	-	-	-	-	-	5	815.075.2	5,9



Viroles de continuité de masse, en acier galvanisé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
A	B	C	D	E						
-	3/8"	10,2	-	-	-	-	-	10	815.011.0	0,4
-	1/2"	13,9	-	-	-	-	-	10	815.016.0	0,6
-	3/4"	18,5	-	-	-	-	-	5	815.021.0	0,8
-	1"	23,8	-	-	-	-	-	5	815.029.0	1,4




Viroles de continuité de masse, en laiton nickelé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
A	B	C	D	E						
-	1/4"	5,2	-	-	-	-	-	10	815.006.0	0,4
-	5/16"	8,3	-	-	-	-	-	10	815.010.0	0,8
-	3/8"	10,2	-	-	-	-	-	10	815.011.3	0,6
-	1/2"	13,9	-	-	-	-	-	10	815.016.3	0,8
-	3/4"	18,5	-	-	-	-	-	5	815.021.3	1,4
-	1"	23,8	-	-	-	-	-	5	815.029.3	2,8
-	1.1/4"	31,8	-	-	-	-	-	2	815.036.3	6
-	1.1/2"	36,8	-	-	-	-	-	2	815.042.3	6,8
-	2"	47,8	-	-	-	-	-	2	815.048.3	8,8


ACCESSOIRES POUR RACCORDS EN LAITON NICKELÉ



Joint d'étanchéité en néoprène pour raccords de type ISO



FILETAGE ISO	FILETAGE PG	FILETAGE NPT	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
M16 x 1,5	-	-	1,2	-	20	14	-	100	815.416.0	0,03
M20 x 1,5	-	-	1,2	-	24	18	-	100	815.420.0	0,03
M25 x 1,5	-	-	1,2	-	30	23	-	50	815.425.0	0,05
M32 x 1,5	-	-	1,2	-	40	30	-	50	815.432.0	0,11
M40 x 1,5	-	-	1,2	-	48	38	-	50	815.440.0	0,15
M50 x 1,5	-	-	1,2	-	58	48	-	50	815.450.0	0,19
M63 x 1,5	-	-	1,2	-	75	61	-	50	815.463.0	0,33



Joint d'étanchéité en néoprène pour raccords de types Pg / NPT



FILETAGE ISO	FILETAGE PG	FILETAGE NPT	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
-	Pg 7	-	1,2	-	17	11,5	-	100	815.507.0	0,03
-	Pg 9	-	1,2	-	20	14	-	100	815.509.0	0,03
-	Pg 11	-	1,2	-	23	17	-	100	815.511.0	0,03
-	Pg 13,5	-	1,2	-	25	19	-	100	815.513.0	0,04
-	Pg 16	NPT 1/2"	1,2	-	27	21	-	100	815.516.0	0,05
-	Pg 21	NPT 3/4"	1,2	-	34	26,5	-	50	815.521.0	0,07
-	Pg 29	NPT 1"	1,2	-	45	35	-	50	815.529.0	0,13
-	Pg 36	NPT 1.1/4"	1,2	-	56	45	-	50	815.536.0	0,19
-	Pg 42	NPT 1.1/2"	1,2	-	67	52	-	50	815.542.0	0,3
-	Pg 48	NPT 2"	1,2	-	72	58	-	50	815.548.0	0,34

Raccords
spéciaux



Joint d'étanchéité en nitrile (NBR) pour raccord de type NPT



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
NPT 1/2"	1/2"	-	-	-	-	-	-	50	815.616.0	0,03
NPT 3/4"	3/4"	-	-	-	-	-	-	25	815.620.0	0,05
NPT 1"	1"	-	-	-	-	-	-	25	815.626.0	0,11
NPT 1.1/4"	1.1/4"	-	-	-	-	-	-	10	815.635.0	0,15
NPT 1.1/2"	1.1/2"	-	-	-	-	-	-	10	815.640.0	0,19
NPT 2"	2"	-	-	-	-	-	-	10	815.650.0	0,33
NPT 2.1/2"	2.1/2"	-	-	-	-	-	-	10	815.663.0	0,45
NPT 3"	3"	-	-	-	-	-	-	10	815.675.0	0,6

ACCESSOIRES POUR RACCORDS EN LAITON NICKELÉ

Contre-écrous ISO en laiton nickelé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
M16 x 1,5	-	-	3	-	20	-	-	50	880.112.0	0,4
M16 x 1,5	-	-	3	-	20	-	-	50	880.116.0	0,4
M20 x 1,5	-	-	3,5	-	24	-	-	50	880.120.0	0,6
M25 x 1,5	-	-	3,5	-	30	-	-	25	880.125.0	0,9
M32 x 1,5	-	-	4,5	-	35	-	-	20	880.132.0	2,2
M40 x 1,5	-	-	4,5	-	45	-	-	10	880.140.0	3,2
M50 x 1,5	-	-	5,5	-	55	-	-	10	880.150.0	5
M63 x 1,5	-	-	6	-	70	-	-	5	880.163.0	5,6
M75 x 1,5	-	-	7	-	80	-	-	5	880.175.0	7,5
M90 x 2,0	-	-	8	-	100	-	-	5	880.190.0	11

Contre-écrous Pg en laiton nickelé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
Pg 7	-	-	2,9	-	15	-	-	50	880.007.0	0,2
Pg 9	-	-	2,9	-	18	-	-	50	880.009.0	0,2
Pg 11	-	-	2,9	-	21	-	-	50	880.011.0	0,3
Pg 13,5	-	-	3,1	-	23	-	-	50	880.013.0	0,4
Pg 16	-	-	3,1	-	26	-	-	50	880.016.0	0,5
Pg 21	-	-	3,6	-	32	-	-	20	880.021.0	0,8
Pg 29	-	-	4,1	-	41	-	-	20	880.029.0	1,4
Pg 36	-	-	5,1	-	51	-	-	10	880.036.0	2,1
Pg 42	-	-	5,1	-	60	-	-	5	880.042.0	3,6
Pg 48	-	-	5,6	-	64	-	-	5	880.048.0	4,1

Contre-écrous NPT en laiton nickelé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
NPT 1/2"	-	-	4	-	27	-	-	50	880.216.0	1,1
NPT 3/4"	-	-	4,5	-	32	-	-	25	880.220.0	1,4
NPT 1"	-	-	6	-	38	-	-	25	880.226.0	2,1
NPT 1.1/4"	-	-	6,5	-	48	-	-	5	880.235.0	3,5
NPT 1.1/2"	-	-	7	-	55	-	-	5	880.240.0	5
NPT 2"	-	-	7,5	-	70	-	-	5	880.250.0	8,8

ACCESSOIRES POUR RACCORDS EN LAITON NICKELÉ



Contre-écrous NPT "tiger grip" en acier galvanisé



FILETAGE	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
A	B	C	D	E						
NPT 1/2"	-	-	-	-	-	-	-	100	880.316.0	0,5
NPT 3/4"	-	-	-	-	-	-	-	50	880.320.0	0,8
NPT 1"	-	-	-	-	-	-	-	50	880.326.0	1,3
NPT 1.1/4"	-	-	-	-	-	-	-	20	880.335.0	1,8
NPT 1.1/2"	-	-	-	-	-	-	-	20	880.340.0	2,2
NPT 2"	-	-	-	-	-	-	-	20	880.350.0	2,8
NPT 2.1/2"	-	-	-	-	-	-	-	10	880.363.0	3,5
NPT 3"	-	-	-	-	-	-	-	10	880.375.0	5,6



Agrandisseurs Pg / Pg en laiton nickelé




FILETAGE	FILETAGE	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
A	B	C	D	E						
Pg 7	Pg 9	-	15	5	17	-	-	50	882.009.0	0,7
Pg 9	Pg 11	-	16,5	6	20	-	-	50	882.011.0	0,9
Pg 9	Pg 13,5	-	17,5	6	22	-	-	50	882.012.0	1,1
Pg 11	Pg 13,5	-	17,5	6	22	-	-	50	882.013.0	1,2
Pg 11	Pg 16	-	19	6,5	24	-	-	25	882.016.0	1,2
Pg 13,5	Pg 16	-	18,5	6	24	-	-	25	882.017.0	1,3
Pg 13,5	Pg 21	-	21	6,5	30	-	-	20	882.018.0	2,3
Pg 16	Pg 21	-	21	6,5	30	-	-	20	882.021.0	2,4
Pg 21	Pg 29	-	23	7	39	-	-	15	882.029.0	3,7
Pg 29	Pg 36	-	28	8	50	-	-	10	882.036.0	7,4
Pg 36	Pg 42	-	31	9	57	-	-	10	882.042.0	9,3
Pg 42	Pg 48	-	33	10	64	-	-	10	882.048.0	14,7



Adaptateurs Pg / ISO en laiton nickelé




FILETAGE	FILETAGE	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
A	B	C	D	E						
Pg 11	M16 x 1,5	A	11	6,5	22	-	-	50	882.111.0	1,3
Pg 16	M20 x 1,5	A	16	7	27	-	-	50	882.116.0	3,2
Pg 21	M25 x 1,5	B	13	8	32	-	-	20	882.121.0	3,8
Pg 29	M32 x 1,5	B	14	8,5	40	-	-	20	882.129.0	8
Pg 36	M40 x 1,5	B	15	8,5	55	-	-	10	882.136.0	12,4
Pg 48	M50 x 1,5	B	17	10	65	-	-	5	882.148.0	17,2



ACCESSOIRES POUR RACCORDS EN LAITON NICKELÉ




Réducteurs Pg / Pg en laiton nickelé



FILETAGE EXTÉRIEUR	FILETAGE INTÉRIEUR	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
Pg 9	Pg 7	-	8	5	17	-	-	100	881.007.0	0,4
Pg 11	Pg 7	-	9	6	19	-	-	100	881.008.0	0,7
Pg 11	Pg 9	-	9	6	19	-	-	100	881.009.0	0,9
Pg 13,5	Pg 9	-	9	6	21	-	-	100	881.010.0	0,9
Pg 13,5	Pg 11	-	9	6	21	-	-	100	881.011.0	0,9
Pg 16	Pg 11	-	9	6	23	-	-	100	881.012.0	0,9
Pg 16	Pg 13,5	-	9	6	23	-	-	100	881.013.0	1,2
Pg 21	Pg 13,5	-	10	7	29	-	-	50	881.015.0	2,1
Pg 21	Pg 16	-	10	7	29	-	-	50	881.016.0	1,8
Pg 29	Pg 21	-	11	8	39	-	-	25	881.021.0	3,7
Pg 36	Pg 29	-	11	8	50	-	-	25	881.029.0	5,7
Pg 42	Pg 36	-	14	10	64	-	-	25	881.036.0	6,5
Pg 48	Pg 42	-	14	10	64	-	-	25	881.042.0	7,7



Agrandisseurs ISO / ISO en laiton nickelé



FILETAGE EXTÉRIEUR	FILETAGE INTÉRIEUR	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
M12 x 1,5	M16 x 1,5	-	15	5	18	-	-	50	881.216.0	1,2
M16 x 1,5	M20 x 1,5	-	18	6	22	-	-	50	881.220.0	1,5
M20 x 1,5	M25 x 1,5	-	19	7	27	-	-	50	881.225.0	2,5
M25 x 1,5	M32 x 1,5	-	21	8	34	-	-	20	881.232.0	2,9
M32 x 1,5	M40 x 1,5	-	23	8	42	-	-	20	881.240.0	4,5
M32 x 1,5	M50 x 1,5	-	31	9	53	-	-	10	881.245.0	6
M40 x 1,5	M50 x 1,5	-	31	9	53	-	-	10	881.250.0	7,7
M50 x 1,5	M63 x 1,5	-	24	10	65	-	-	5	881.263.0	7,8




Adaptateurs ISO / Pg en laiton nickelé



A




B



C

FILETAGE EXTÉRIEUR	FILETAGE INTÉRIEUR	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
M12 x 1,5	Pg 7	A	17	7	14	-	-	100	881.107.0	0,8
M16 x 1,5	Pg 9	A	18	7	18	-	-	50	881.109.0	0,9
M20 x 1,5	Pg 11	A	18	7	22	-	-	50	881.111.0	1,6
M25 x 1,5	Pg 16	A	22	8	27	-	-	50	881.116.0	2,6
M32 x 1,5	Pg 21	A	24	9	34	-	-	20	881.121.0	4
M40 x 1,5	Pg 29	B	14	9	42	-	-	10	881.129.0	8,6
M50 x 1,5	Pg 36	B	16	10	52	-	-	10	881.136.0	12,3
M63 x 1,5	Pg 48	A	33	11	65	-	-	1	881.148.0	22,5


ACCESSOIRES POUR RACCORDS EN LAITON NICKELÉ



Réducteurs ISO / ISO en laiton nickelé




FILETAGE EXTÉRIEUR	FILETAGE INTÉRIEUR	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
M16 x 1,5	M12 x 1,5	-	10	7	20	-	-	50	882.212.0	1,2
M20 x 1,5	M16 x 1,5	-	10	7	24	-	-	50	882.216.0	1,5
M25 x 1,5	M20 x 1,5	-	12	8	30	-	-	20	882.220.0	2,6
M32 x 1,5	M25 x 1,5	-	13	9	36	-	-	20	882.225.0	4,5
M40 x 1,5	M32 x 1,5	-	13	9	42	-	-	10	882.232.0	6,9
M50 x 1,5	M40 x 1,5	-	15	10	55	-	-	5	882.240.0	11,8
M63 x 1,5	M50 x 1,5	-	18	11	70	-	-	1	882.250.0	22,1



Adaptateurs NPT / Pg en laiton nickelé



FILETAGE EXTÉRIEUR	FILETAGE INTÉRIEUR	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
NPT 1/2"	Pg 9	-	-	-	-	-	-	50	882.309.0	2,9
NPT 1/2"	Pg 11	-	-	-	-	-	-	50	882.311.0	2,9
NPT 1/2"	Pg 13,5	-	-	-	-	-	-	50	882.313.0	3,2
NPT 1/2"	Pg 16	-	-	-	-	-	-	50	882.316.0	3,3
NPT 3/4"	Pg 21	-	-	-	-	-	-	50	882.321.0	8
NPT 1"	Pg 21	-	-	-	-	-	-	20	882.326.0	11,6
NPT 1"	Pg 29	-	-	-	-	-	-	20	882.329.0	13,8
NPT 1 1/4"	Pg 29	-	-	-	-	-	-	20	882.330.0	20,2
NPT 1 1/4"	Pg 36	-	-	-	-	-	-	10	882.336.0	22,3
NPT 1 1/2"	Pg 36	-	-	-	-	-	-	10	882.340.0	22,5
NPT 1 1/2"	Pg 42	-	-	-	-	-	-	5	882.342.0	23,8
NPT 2"	Pg 48	-	-	-	-	-	-	5	882.348.0	24,1



Adaptateurs Pg / NPT en laiton nickelé




FILETAGE EXTÉRIEUR	FILETAGE INTÉRIEUR	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
Pg 9	NPT 1/2"	-	-	-	-	-	-	50	882.410.0	3,1
Pg 11	NPT 3/8"	-	-	-	-	-	-	50	882.411.0	3,1
Pg 11	NPT 1/2"	-	-	-	-	-	-	50	882.412.0	2,8
Pg 13,5	NPT 1/2"	-	-	-	-	-	-	50	882.413.0	2,8
Pg 16	NPT 1/2"	-	-	-	-	-	-	50	882.416.0	3,8
Pg 21	NPT 3/4"	-	-	-	-	-	-	20	882.420.0	3,8
Pg 29	NPT 1 1/4"	-	-	-	-	-	-	20	882.435.0	8
Pg 36	NPT 1 1/2"	-	-	-	-	-	-	10	882.440.0	17
Pg 48	NPT 2"	-	-	-	-	-	-	5	882.450.0	22

ACCESSOIRES POUR RACCORDS EN LAITON NICKELÉ




Adaptateurs NPT / ISO en laiton nickelé




FILETAGE EXTÉRIEUR	FILETAGE INTÉRIEUR	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
NPT 1/2"	M16 x 1,5	-	-	-	-	-	-	50	882.516.0	3,1
NPT 1/2"	M20 x 1,5	-	-	-	-	-	-	50	882.520.0	3,2
NPT 1/2"	M25 x 1,5	-	-	-	-	-	-	50	882.522.0	2,8
NPT 1/2"	M32 x 1,5	-	-	-	-	-	-	50	882.523.0	3,5
NPT 3/4"	M20 x 1,5	-	-	-	-	-	-	50	882.524.0	4,7
NPT 3/4"	M25 x 1,5	-	-	-	-	-	-	50	882.525.0	8,9
NPT 3/4"	M32 x 1,5	-	-	-	-	-	-	10	882.527.0	9
NPT 1"	M25 x 1,5	-	-	-	-	-	-	20	882.528.0	9,2
NPT 1"	M32 x 1,5	-	-	-	-	-	-	20	882.532.0	12
NPT 1 1/4"	M25 x 1,5	-	-	-	-	-	-	20	882.536.0	20
NPT 1 1/4"	M32 x 1,5	-	-	-	-	-	-	10	882.538.0	22
NPT 1 1/4"	M40 x 1,5	-	-	-	-	-	-	20	882.540.0	28
NPT 1 1/2"	M40 x 1,5	-	-	-	-	-	-	1	882.548.0	36
NPT 1 1/2"	M50 x 1,5	-	-	-	-	-	-	1	882.550.0	40
NPT 1 1/2"	M63 x 1,5	-	-	-	-	-	-	1	882.552.0	44
NPT 2"	M50 x 1,5	-	-	-	-	-	-	1	882.560.0	-
NPT 2"	M63 x 1,5	-	-	-	-	-	-	1	882.563.0	-

Adaptateurs ISO / NPT en laiton nickelé



FILETAGE EXTÉRIEUR	FILETAGE INTÉRIEUR	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
M16 x 1,5	NPT 1/2"	-	-	-	-	-	-	50	882.612.0	3,8
M20 x 1,5	NPT 1/2"	-	-	-	-	-	-	50	882.616.0	8,9
M25 x 1,5	NPT 3/4"	-	-	-	-	-	-	20	882.620.0	7,3
M32 x 1,5	NPT 1"	-	-	-	-	-	-	10	882.626.0	7,5


ACCESSOIRES POUR RACCORDS EN LAITON NICKELÉ



Raccords de jonction de gaine, en laiton nickelé, IP 67




SEALTITE DIAMÈTRE (POUCES)	SEALTITE DIAMÈTRE (POUCES)	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
5/16"	5/16"	8,3	41	-	26	-	24	10	784.010.0	7,4
3/8"	3/8"	10,4	41	-	26	-	24	10	784.012.0	7,4
1/2"	1/2"	13,8	45	-	29	-	27	10	784.016.0	8,8
3/4"	3/4"	18,5	48	-	35	-	33	5	784.020.0	13
1"	1"	23,8	53	-	45	-	44	5	784.026.0	25,2
1.1/4"	1.1/4"	31,9	58	-	53	-	50	2	784.035.0	32,6
1.1/2"	1.1/2"	36,9	69	-	62	-	58	2	784.040.0	52,4
2"	2"	47,9	78	-	76	-	72	2	784.050.0	76,3



Adaptateur tournant, ISO, filetage intérieur / extérieur, en laiton nickelé, IP 54



FILETAGE EXTÉRIEUR	FILETAGE INTÉRIEUR	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
M16 x 1,5	M16 x 1,5	8,5	39	10	21	-	21	10	885.216.0	6,2
M20 x 1,5	M20 x 1,5	12	42	10	25	-	25	10	885.220.0	9,2
M25 x 1,5	M25 x 1,5	17,5	42	10	31	-	31	5	885.225.0	11,2
M32 x 1,5	M32 x 1,5	22,5	45	12	38	-	38	5	885.232.0	17,2
M40 x 1,5	M40 x 1,5	28	54	14	48	-	48	2	885.240.0	36,8




Adaptateur tournant, ISO, filetage intérieur / extérieur, en laiton nickelé, IP 67



FILETAGE EXTÉRIEUR	FILETAGE INTÉRIEUR	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
M16 x 1,5	M16 x 1,5	10,4	42	12	22	-	22	10	885.216.1	6,8
M20 x 1,5	M20 x 1,5	13,9	44	13	27	-	27	10	885.220.1	10,2
M25 x 1,5	M25 x 1,5	17,4	48	15	33	-	33	5	885.225.1	16
M32 x 1,5	M32 x 1,5	23,4	48	15	40	-	40	5	885.232.1	21
M40 x 1,5	M40 x 1,5	29,4	51	16	48	-	48	2	885.240.1	30,8

ACCESSOIRES POUR RACCORDS EN LAITON NICKELÉ



Adaptateur coudé à 90°, ISO, filetage intérieur / extérieur, en laiton nickelé




FILETAGE EXTÉRIEUR	FILETAGE INTÉRIEUR	DIAM. INTÉRIEUR MINI. (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
M16 x 1,5	M16 x 1,5	-	26	10	-	24	22	10	783.016.0	6
M20 x 1,5	M20 x 1,5	-	26	10	-	25	24	10	783.020.0	10
M25 x 1,5	M25 x 1,5	-	32	10	-	34	33	5	783.025.0	16
M32 x 1,5	M32 x 1,5	-	40	12	-	40	42	5	783.032.0	26
M40 x 1,5	M40 x 1,5	-	46	13	-	45	52	5	783.040.0	37
M50 x 1,5	M50 x 1,5	-	52	14	-	51,5	60	5	783.050.0	52



Chapeau d'extrémité en néoprène, avec décharge de traction, IP 54



FILETAGE	SEALTITE DIAMÈTRE (POUCHES)	DIAMÈTRE DE SERRAGE (MM)	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
-	3/8"	4 - 9	33	-	-	-	-	3000	266.812.0	0,3
-	1/2"	5 - 12	34	-	-	-	-	2400	266.817.0	0,6
-	3/4"	7 - 17	47	-	-	-	-	1200	266.823.0	1,1
-	1"	9 - 20	48	-	-	-	-	800	266.829.0	1,4
-	1.1/4"	16 - 30	47	-	-	-	-	800	266.836.0	1,9



Bagues de mise à la terre en laiton nickelé pour types ISO / NPT



FILETAGE ISO	FILETAGE PG	FILETAGE NPT	DIMENSIONS EN MM					CONDITION. STANDARD	RÉFÉRENCE	POIDS (KG/100)
			A	B	C	D	E			
M16 x 1,5	-	-	25	16	13	6,2	30	50	880.610.0	-
M20 x 1,5	-	-	29	20	13	6,2	33	50	880.612.0	-
M25 x 1,5	-	-	34	25	13	6,2	36	50	880.613.0	-
M32 x 1,5	-	-	42	32	22	12,2	41	50	880.620.0	-
M40 x 1,5	-	-	54	40	26	14,2	47	50	880.627.0	-
M50 x 1,5	-	-	67	50	29	14,2	64	50	880.635.0	-
M63 x 1,5	-	-	77	63	29	14,2	73	50	880.650.0	-
-	-	NPT 1/2"	29	22	13	6,2	33	50	880.716.0	-
-	-	NPT 3/4"	34	27	13	6,2	36	50	880.720.0	-
-	-	NPT 1"	42	34	22	12,2	41	50	880.726.0	-
-	-	NPT 1.1/4"	54	42	26	14,2	47	50	880.735.0	-
-	-	NPT 1.1/2"	67	49	29	14,2	64	50	880.740.0	-
-	-	NPT 2"	77	61	29	14,2	73	50	880.750.0	-