

PRODUCT-DETAILS

B21 312-100

B21 312-100, Energy meter'Silver', Modbus RS485, Single-phase, 5 A



Informations générales

Extension du type de produit	B21 312-100
Code de produit	2CMA100155R1000
ABB désignation de type	B21 312-100
EAN	7392696001557
Description courte	B21 312-100, Energy meter'Silver', Modbus RS485, Single-phase, 5 A

Description longue	Advanced compact DIN-rail meter with an easy to read back lighted display. The meter is intended for use in the commercial or residential buildings etc. The meter can be used in 3 or 4 wire systems. The meter has several instrumentation values, 25 possible alarms and event logs. Single phase direct connected for active and reactive energy. Import and export of energy in different registers and one total. Resettable register for intermediate values. Up to four tariffs. Two outputs and inputs for pulses or alarm etc. RS-485 communication over Modbus RTU or EQ Bus. Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + MID approved and verified.
--------------------	--

Eco Transparence

Environmental Product Declaration - EPD	9AKK108467A4138
---	-----------------

Technique

Normes et standards	IEC 62053-23
Fonction	Electricity meter
Sub-Function	Silver
Tension nominale (U_n)	220-240 V
Voltage Range	176...276 V
Courant nominal (I_n)	5 A Maximum 65 A
Intensité de courant	5 A
Fréquence assignée (f)	50 / 60 Hz
	0.414 W
Interface de communication	Modbus RS485
Précision	Active Energy Class B MID ($\pm 1\%$)
Measuring Instrument Conformity	Measurement Instrument Directive (MID)
Meter Tariff Control	External
Meter Tariff Rating	Multi-Tariff
Pulse Output Rate	1-999999
Nombre de pôles	1
Nombre de phases	Single-phase
Number of Counter Positions	7
Nombre d'entrées/sorties numériques	2 DI 2 DO
Meter Type	Direct connected
Type de montage	DIN rail
Pulse Output Type	Electrical
Type d'affichage	Digital
Matériau du boîtier	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.
Option E/S	2 digital output, 2 digital input
Communication	Modbus RTU
Connecting Capacity Main Circuit	1 ... 25 mm ²

Environnement

Température de l'air ambiant	Operation -40 ... 70 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Informations RoHS	2CMC485005
Informations environnementales	2CMC485004D0001
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Width in Number of Modular Spacings	2
Produit Largeur Net	35 mm
Produit Hauteur Net	26.5 mm
Produit Longueur Net	65 mm
Poids net	0.15 kg
Taille	97X35X65

Commande

Quantité minimum	1 pièce
Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Poids	0.20 kg
Code douanier	90283011
E-Number (Finland)	6625031
E-Number (Sweden)	0900034
Pays d'origine	Italy (IT)

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CMC485001D0001
--------------------------------	-----------------

Classifications

ETIM 8	EC001506 - Kilowatt-hour meter
ETIM 9	EC001506 - Kilowatt-hour meter
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90283011
eClass	V11.0 : 27142316
Code de classification d'objet	P

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CCG000242R0001	SCU100 Control unit	SCU100	1	piece
2CDG110226R0011	QA/S3.16.1 Energy Analyzer, M-Bus, 16 Devices, MDRC	QA/S3.16.1	1	piece
2CDG110227R0011	QA/S3.64.1 Energy Analyzer, M-Bus, 64 Devices, MDRC	QA/S3.64.1	1	piece
2CDG110228R0011	QA/S4.16.1 Energy Analyzer, Modbus RTU, 16 Devices, MDRC	QA/S4.16.1	1	piece
2CDG110229R0011	QA/S4.64.1 Energy Analyzer, Modbus RTU, 64 Devices, MDRC	QA/S4.64.1	1	piece
2CDG110224R0011	QA/S1.16.1 Energy Analyzer, KNX, 16 Devices, MDRC	QA/S1.16.1	1	piece

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Compteurs d'énergie → Compteurs d'énergie

