


CADDY ISOL Pipe Support for Cold Installations – ISOL089 (142520)



- With integrated steel pipe clamp
- Synthetic foam applied to all internal surfaces makes use of sealing kit be superfluous
- $k = 0.049 \text{ W/m} \cdot ^\circ\text{K}$ (a 0°C)
- Fire rating B2 acc. to DIN 4102-1



| | |
|-----------------------------|-----------------------|
| Part Number | ISOL089 |
| Article Number | 142520 |
| Material | Steel Polyurethane |
| Finish | Electrogalvanized |
| Density | 250 kg/m ³ |
| Temperature | -160 to 130 °C |
| Outer Diameter (OD) | 88,9 mm |
| Pipe Size | 3" |
| NB/DN | 80 |
| Gewinde (G) | 1/2" |
| Rod Size (RS) | M10 |
| B | 50 mm |
| E | 30 mm |
| Screw Diameter (Sc) | M8 |
| Static Load (F) | 1 600 N |
| Standard Packaging Quantity | 1 pc |
| UPC | 78285680793 |
| EAN-13 | 8711893088137 |

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2015 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

