



LarK-111



LarK-111 · HONEYCOMB LOUVER



reddot design award
winner 2014



LarK-111						P	CCT	Beam	I	Flux	Flux Out	LOR
PHASE CUT *	A25	☉	-10-10-	W N Z		6,5W	2700K	19°	200mA	900Lm	828Lm	92%
	A25	☉	-10-11-	W N Z		6,5W	3000K	19°	200mA	940Lm	865Lm	92%
	A25	☉	-10-12-	W N Z		6,5W	4000K	19°	200mA	950Lm	874Lm	92%
	A25	☉	-10-20-	W N Z		6,5W	2700K	40°	200mA	900Lm	774Lm	86%
	A25	☉	-10-21-	W N Z		6,5W	3000K	40°	200mA	940Lm	808Lm	86%
	A25	☉	-10-22-	W N Z		6,5W	4000K	40°	200mA	950Lm	817Lm	86%
	A25	☉	-20-10-	W N Z		12W	2700K	19°	350mA	1440Lm	1325Lm	92%
	A25	☉	-20-11-	W N Z		12W	3000K	19°	350mA	1500Lm	1380Lm	92%
	A25	☉	-20-12-	W N Z		12W	4000K	19°	350mA	1520Lm	1398Lm	92%
	A25	☉	-20-20-	W N Z		12W	2700K	40°	350mA	1440Lm	1238Lm	86%
PHASE CUT *	A25	☉	-20-21-	W N Z		12W	3000K	40°	350mA	1500Lm	1290Lm	86%
	A25	☉	-20-22-	W N Z		12W	4000K	40°	350mA	1520Lm	1307Lm	86%
	A25	☉	-21-10-	W N Z		12W	2700K	19°	350mA	1440Lm	1325Lm	92%
	A25	☉	-21-11-	W N Z		12W	3000K	19°	350mA	1500Lm	1380Lm	92%
	A25	☉	-21-12-	W N Z		12W	4000K	19°	350mA	1520Lm	1398Lm	92%
DALI PUSH *	A25	☉	-21-20-	W N Z		12W	2700K	40°	350mA	1440Lm	1238Lm	86%
	A25	☉	-21-21-	W N Z		12W	3000K	40°	350mA	1500Lm	1290Lm	86%
	A25	☉	-21-22-	W N Z		12W	4000K	40°	350mA	1520Lm	1307Lm	86%
	A25	☉	-21-22-	W N Z		12W	4000K	40°	350mA	1520Lm	1307Lm	86%



220
240V~



CRI>90 | L80B10
> 60.000h




☉ OPTIONS


2	LarK-111
3	LarK-111 Honeycomb**

* OTHER DIM OPTIONS PLEASE CONSULT | ** Honeycomb affects lighting parameters

LarK-111



LarK-111 · HONEYCOMB LOUVER



COLOUR | W □ RAL 9016 | N ■ RAL 9005 | Z ■ RAL 9006 |

MATERIAL | AL |

Bluetooth & Wi-Fi » PLEASE CONSULT

Calle N · Pol. Ind. EL OLIVERAL
46394 Ribarroja del Turia · Valencia (Spain)
Tel. +34 961 667 207 · Fax +34 961 667 054
info@arkoslight.com · www.arkoslight.com

5Year
GUARANTEE*