

4G2,5² : the unmissable

P515



9 meters
4G2,5mm² - H05VV-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P811



15 meters
4G2,5mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P812



20 meters
4G2,5mm² - H05VV-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

S8V04



31 meters
4G2,5mm² - H07RN-F
STEEL open case
Ratchet removable
Horizontal and vertical use
Options : data sheet STEEL 800

S8H07



41 meters
4G2,5mm² - H07RN-F
STEEL open case
Ratchet removable
Horizontal use
Options : data sheet STEEL 800

S8H09



55 meters
4G2,5mm² - H07RN-F
STEEL open case
Ratchet in option
Horizontal use
Options : data sheet STEEL 800

Model	Total lenght	Cable type	IP	kW (20°C) 		kW (20°C) 		Slipring capacity	Thermal Protector	Incoming cable	Dimensions (mm)	Art.
P515	9 m	H05VV-F	42	400V	2,0	400V	2,7	-	-	-	H290xI350xP160	ER04025-09V-P515
P811	15 m	H07RN-F					3,0				H380xI470xP205	ER04025-15R-P811
P812	20 m	H05VV-F					32 A					ER04025-20V-P812
S8V04	31 m	H07RN-F	65	400V	7,0	400V	10,0	-	-	2,5 m	Ø440xP365	ER04025-31R-S8V04
S8H07	41 m				6,0		8,5				ER04025-41R-S8H07	
S8H09	55 m				Ø550xP395		ER04025-55R-S8H09					