

5G2,5² : the unmissable

P520



7 meters
5G2,5mm² - IGUS CF77
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P815



12 meters
5G2,5mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P816



17 meters
5G2,5mm² - H05VV-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

S8V28



22 meters
5G2,5mm² - H07RN-F
STEEL open case
Ratchet removable
Horizontal and vertical use
Options : data sheet STEEL 800

S8H33



31 meters
5G2,5mm² - H07RN-F
STEEL open case
Ratchet removable
Horizontal use
Options : data sheet STEEL 800

S8H35



55 meters
5G2,5mm² - H07RN-F
STEEL open case
Ratchet in option
Horizontal use
Options : data sheet STEEL 800

Model	Total length	Cable type	IP	kW (20°C)		kW (20°C)		Thermal Protector	Slipping capacity	Incoming cable	Dimensions (mm)	Art.
P520	7 m	IGUS CF77	42	400V	2,0	400V	2,7	10 A	-	-	H290xI350xP160	ER05025-07P-P520
P815	12 m	H07RN-F					3,0	-			H380xI470xP205	ER05025-12R-P815
P816	17 m	H05VV-F										ER05025-17V-P816
S8V28	22 m	H07RN-F	65	400V	7,0	400V	9,5	32 A	-	2,5 m	Ø440xP365	ER05025-22R-S8V28
S8H33	31 m										Ø550xP365	ER05025-31R-S8H33
S8H35	55 m				6,0		8,5				Ø550xP395	ER05025-55R-S8H35