

PRODUCT-DETAILS

OTM40F4CB21D400C

OTM40F4CB21D400C AUTOMATIC TRANSFER SWITCH



Informations générales

Extension du type de produit	OTM40F4CB21D400C
Code de produit	1SCA150580R1001
EAN	6417019807072
Description courte	OTM40F4CB21D400C AUTOMATIC TRANSFER SWITCH
Description longue	Automatic transfer switch, motor operated, open transition type 1-0-2. Self-supplied unit with adjustable operating parameters.

Commande

Code douanier	85365080
Pays d'origine	China (CN)

Downloads Préférés

Fiche produit, informations techniques	1SCC308001B0201
Instructions et manuels	2TFR700025A1001
Mechanical Drawings	OTM40-125_4P_COMPACTATS

Dimensions

Produit Hauteur Net	103 mm
Produit Longueur Net	131 mm
Poids net	2.11 kg

Technique

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 40 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 40 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 40 A
Rated Operational Current AC-31B (I_e)	(380 ... 415 V) 40 A
Rated Operational Current AC-32B (I_e)	(380 ... 415 V) 40 A
Rated Operational Current AC-33B (I_e)	(380 ... 415 V) 40 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 18.5 kW
Courant thermique conventionnel à l'air libre (I_{th})	q = 40 °C 40 A
Tension assignée de tenue aux chocs (U_{imp})	8 kV
Tension assignée d' isolement (U_i)	800 V
Tension	380...415 V AC
Courant assigné de courte durée admissible (I_{cw})	for 1 s 2.5 kiloampere rms
Motor Operational Voltage	380...415 V AC
Power Loss	1.6 W
Degré de pollution	3
Handle Type	Direct mounted handle
Fourth Pole Type	Switched - Simultaneous Function
Position of Line Terminals	Supplies on Bottom - Load on Top
Controller Type	21D
Nombre de pôles	4
Indice de protection	Front IP20
Transition Type	Open

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	No declaration needed
Instructions et manuels	2TFR700025A1001

Emballage

Emballage Niveau 1 Unités	1 pièce
Emballage Niveau 1 Largeur	103 mm
Emballage Niveau 1 Longueur	328 mm
Emballage Niveau 1 Hauteur	168 mm
Emballage Niveau 1 Poids	2.35 kg

Classifications

ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - sectionneur de charge
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3640450

Catégories

Produits basse tension → Interrupteurs → Inverseurs de sources et by-pass → Compact ATS

