

PRODUCT-DETAILS

UD/S6.210.2.1

UD/S6.210.2.1 LED-Dim actuator 6x210W



Informations générales

Extension du type de produit	UD/S6.210.2.1
Code de produit	2CKA006197A0049
EAN	4011395251881
Description courte	UD/S6.210.2.1 LED-Dim actuator 6x210W

Description longue	<p>Multichannel universal dimming actuator optimised for dimming retrofit LED lamps (LEDi). Also suitable for dimming incandescent lamps, low-voltage halogen lights with conventional or electronic transformers, 230 V halogen lamps and dimmable energy-saving halogen lamps. Automatic load detection (can be deactivated). Separate N-connection per channel. Parallel connection of the outputs possible to increase the output power. Outputs can be connected in parallel in any configuration. Minimum load: 2 W. Manual operation on device also possible without bus voltage or in an unprogrammed status. Programming of the device also possible without applied 230V supply voltage. Extensive test and diagnosis functions for the i-Bus tool. Fast parameter setting in ETS using copyable channel templates. With integrated bus coupler. Nominal power at 230 V~ mains voltage: 230 V~ incandescent and halogen lamps: 6 x 210 W/VA to 1 x 800 W/VA. Dimmable 230 V~ LEDi: 6 x 210 W/VA to 1 x 800 W/VA in trailing edge control, 6 x 80 W/VA to 1 x 240 W/VA in leading edge control. Inductive L-transformers with LED/low-voltage halogen lamp: 6 x 210 W/VA to 1 x 800 W/VA. Electronic C-transformers with LED/low-voltage halogen lamp: 6 x 210 W/VA to 1 x 800 W/VA. Electronic LC-transformers with LED/low-voltage halogen lamp: 6 x 80 W/VA to 1 x 240 W/VA.</p>
--------------------	--

Installation

Instructions et manuels	2CKA000073B9628
Type de montage	DIN-Rail

Technique

Fiche produit, informations techniques	No document needed
Data Sheet, Technical Information (Part 2)	2CKA001473B9659
Tension nominale (U_r)	110 ... 230 V
Tension	110...230 V
Auxiliary Voltage AC/DC	110 V AC/DC 230 V AC/DC
Fréquence assignée (f)	50 / 60 Hz
Nombre de sorties	6
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Type de charge	Universal and LED Retrofit
Poids de la batterie	0 g

Material Compliance

Informations RoHS	2CKA200000E4771
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	2CKA309999E9999
REACH Information	True - contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environnement

Température de l'air ambiant	Operation -5 ... +45 °C
Indice de protection	IP20

Dimensions

Width in Number of Modular Spacings	8
Produit Largeur Net	139.6 mm
Produit Hauteur Net	89.4 mm
Produit Longueur Net	62.6 mm
Poids net	459 g
Profondeur d'encastrement (t_2)	63.5 mm

Schéma dimensionnel

2CDC072027F0017

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E2677
Declaration of Conformity - UKCA	2CKA400000E0294

Classifications

ETIM 9	EC001094 - Dimming actuator for bus system
eClass	V11.0 : 27143123
UNSPSC	39121801
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Catégories

Produits basse tension → Home and Building Automation → KNX → Lighting Control → Universal Dim Actuators

