



LED Low Bay Lighting For Harzardous Areas Zone 2/21

Zone 2/21

Lighting under harsh conditions

The industrial low bay lighting NLE in LED technique is especially suited for the specific lighting of machines, production areas or facilities indoor and outdoor under harsh and rough conditions like vibrations, dust, moisture or corrosive atmospheres and extreme temperatures.

Replacement of conventional light fittings up to 150 W

With a luminous flux of the light fittings of up to 8,000 lm this fitting can be used to replace comparable conventional light sources with an equivalent power consumption up to 175 W.

High efficient LED technology

High efficient power LED module and more than 100 Lumen/Watt enables up to 66 % energy-cost savings compared to conventional HID lamp

Application areas

- Heavy Industry
- · Chemical Industry
- Pharmaceutical Industry
- Marine Industry
- Waste water treatment

Energy savings

Model	Equivalent HID Luminaire Energy savings	
NLE		
NLE 3L	70 W - 100 W	Up to 58%
NLE 5L	100 W - 150 W	Up to 66%
NLE 7L	150 W - 175 W	Up to 60%
NLE 8L	150 W - 175 W	Up to 60%





Features

- High-efficient LED module
- Wide temperature range from -40 °C up to +55 °C
- Compact and light weight design for flexible applications
- Available in cold white CCT 5700 K and warm white 3000 K
- High efficient heatsink design for an optimised temperature management
- Impact, anti-shock and vibration resistant
- Mercury- and lead-free for optimal environment protection
- High degree of protection IP66 for harsh environments

Ordering details, Technical data, Polar curve, Dimension drawing

NLE pendant light fitting for Ex-areas Zone 2 and 21

Ordering details



Туре	Lamp / illuminant	Light output	Description	Order No.
NLE industrial	pendant light fitting			
NLE 3L	LED system 30 W ¹)	3.188lm	LED pendant light fitting with swivel bracket	CCL1507006A
NLE 5L	LED system 50 W ¹)	4.829 lm	LED pendant light fitting with swivel bracket	CCL1507138A
NLE 7L	LED system 70 W ¹)	7.322 lm	LED pendant light fitting with swivel bracket	CCL1606204A
NLE 8L	LED system 80 W ¹)	7.869 lm	LED pendant light fitting with swivel bracket	CCL1507402A


¹⁾ Scope of delivery, including LED-system and swivel bracket

Technical data


	NLE
EC-Type Examination Certificate	EPT 16 ATEX 2452X
IECEx Certificate of Conformity	IECEx CQM 16.0013X
Marking accd. to 2014/34/EU	
Marking accd. to IECEx	Ex nR IIC T5/T6 Gc Ex tb IIIC T80°C/100°C Db
Permissible ambient temperature	-40 °C up to +55 °C
Driver lifetime	C10 ~100,000 h at t_a = +25 °C
LED lifetime	L70 ~100,000 h at t_a = +25 °C
Rated voltage	100 - 240 V AC / 108 - 250 V DC
Frequency	0/50 - 60 Hz
Power factor cos φ	≥ 0.9
Circuit	Electronic driver
Protection class	
Lamp / illuminant	LED System
Rated luminous flux	see ordering details
Light colour / CRI	5700 K / R_a >70 (warm white on request)
Dimensions (L x W x H)	250 x 250 x 147 mm
Enclosure colour	grey
Enclosure material	Light alloy, powder coated
Weight	5 kg
Cable glands / gland plates / enclosure drilling	Metal threat 2 x M25 with 1 x plastic plug (M20 on request)
Degree of protection accd. to EN 60529	IP66
Protective cover / protective bowl	Toughened clear glass (opaque glass on request)
Swivel bracket	Sheet steel, painted (stainless steel on request)

Dimension drawing / Polar curve

Polar curve NLE



Dimension drawing NLE





Eaton's Crouse-Hinds Business

The safety you rely on.

See the complete offering of Hazardous and Industrial Products at www.crouse-hinds.de.

U.S. (Global Headquarters): **Eaton's Crouse-Hinds** Business

1201 Wolf Street Syracuse, NY 13208

(866) 764-5454 FAX: (315) 477-5179 FAX Orders Only: (866) 653-0640

CrouseCustomerCTR@Eaton.com

For more information:

If further assistance is required, please contact an authorized Eaton Distributor, Sales Office, or Customer Service Department.

Australia

Phone +61-2-8787-2777 Fax +61-2-9609-2342 crousehindsanz@eaton.com

China

Phone +86-21-2899-3600 Fax +86-21-2899-4055 ECHsales@eaton.com

Great Britain

Phone +44-247-630-89 30 Fax +44-247-630-10 27 sales5@eaton.com

India

Phone +91-124-4683888 Fax +91-124-4683899 cchindia@eaton.com

Canada

Toll Free +1-800-265-0502 +1-800-263-9504 Fax orders only: +1-866-653-0645

Korea

Phone +82-2-3484-6783 Fax +82-2-3484-6778 CCHK-sales@ cooperindustries.com

Mexico/Latin America/ Caribbean

Phone +52-555-804-4000 Fax +52-555-804-4020 mxmercadotecnia@ cooperindustries.com

Spain

Phone +34-9-37362710 Fax +34-9-37835055 sales.CCH.es@ cooperindustries.com

Middle East (Dubai)

Phone +971-4-427-2522 / 2500 +971-4-429-8521 CHMEsales@Eaton.com

The Netherlands

Phone +31-10-2452145 Fax +31-10-2452121 CHRD_mail@Eaton.com

Norway

Phone +47-32-244600 +47-32-244646 Fax CHLIoffice@eaton.com

Singapore:

Phone +65-6645-9888 Fax +65-6297-4819 CHSI-Sales@Eaton.com

Turkey

Phone +90-216-464-20-20 Fax +90-216-464-20-10 infoEGTurkey@eaton.com

Russia

Phone +7-495 510-24-27 Fax +7-495 510-24-28 info@cooper.ru.com www.cooper-russia.ru

Eaton's Crouse-Hinds Business Neuer Weg – Nord 49 D-69412 Eberbach


Phone +49 (0) 6271/806-500 Fax +49 (0) 6271/806-476 E-mail info-ex@eaton.com Internet www.crouse-hinds.de



1000 Eaton Boulevard Cleveland, OH 44122 United States Eaton.com

© 2018 Eaton Corporation All Rights Reserved Printed in Germany Publication No. BR 300 8000 January 2018

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions. Only order confirmations and technical documentation by Eaton is binding. Photos and pictures also do not warrant a specific layout or functionality. Their use in whatever form is subject to prior approval by Eaton. The same applies to Trademarks (especially Eaton, Moeller, and Cutler-Hammer). The Terms and Conditions of Eaton apply, as referenced on Eaton Internet pages and Eaton order confirmations.



1201 Wolf Street Syracuse, NY 13208 (866) 764-5454 CrouseCustomerCTR@Eaton.com Eaton is a registered trademark.

All other trademarks are property of their respective owners

