



Early-make auxiliary contact for NZM2/3, 1NO, Push-in terminals

Part no. NZM2/3-XHIV-PI
189748
EL Number 4363008
(Norway)

General specifications		
Product name		Eaton Moeller series NZM auxiliary contact
Part no.		NZM2/3-XHIV-PI
EAN		4015081877430
Product Length/Depth		115 millimetre
Product height		65 millimetre
Product width		75 millimetre
Product weight		0.06 kilogram
Compliances		RoHS conform
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Auxiliary contact
Delivery program		
Special features		C300/R300 (auxiliary contacts, UL/CSA, pilot duty)
Technical Data - Electrical		
Voltage rating at DC		220 V DC
Voltage rating at AC		500 V AC
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V		4 A
Conventional thermal current Ith of auxiliary contacts		4 A
Technical Data - Mechanical		
Mounting Method		Other
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		0
Number of contacts (normally open contacts)		1
Connection type		Screw connection
Lamp holder		None
Special features		C300/R300 (auxiliary contacts, UL/CSA, pilot duty)
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information			
Model			Integrable

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecI@ss13-27-37-13-02 [AKN342018])			
Number of contacts as change-over contact			0
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			0
Number of fault-signal switches			0
Rated operation current Ie at AC-15, 230 V		A	4
Type of electric connection			Screw connection
Model			Integrable
Mounting method			Other
Lamp holder			None