

PRODUCT-DETAILS

E232E-8/230-MULTI1

E232E-8/230-MULTI1 Staircase Switch



Informations générales

Extension du type de produit	E232E-8/230-MULTI1
Code de produit	2CDE010013R0511
EAN	4016779654197
Description courte	E232E-8/230-MULTI1 Staircase Switch

Description longue	Staircase time switches with off-delay are operated by push-buttons, which are often equipped with a glow lamp. The switch levers are designed for a glow lamp current of up to 150 mA and are therefore excellently suited for installations in multistorey buildings. The E 232E-230 staircase lighting timer with off-delay has an electromechanical timer relay with synchronous motor drive, which ensures a high level of operational safety in any installation position. The time range can be set in 15-second increments from one to seven minutes. Can be reswitched after 30s. The multifunctional units of the E 232E-230 Multi 10 and E 232E-8/230 Multi 10 product series have 10 functions that can be set on the front of the unit.
--------------------	---

Technique

Fonction	Electronic
Reset Function	Push Button
Tension nominale (U_r)	230 V AC
Tension d'alimentation	0.85 ... 1.1 V
Additional Control Voltage	8 ... 240 V AC/DC
Maximum Control Current	26 mA

DC

Fréquence assignée (f)	50 ... 60 Hz
Maximum Lamp Load	LED Power > 2W 600 W LED Power < 2W 55 W
Power Loss	6 V·A
Puissance Watt	Filament Lamp 3600 W Fluorescent Lamp Compensated 3600 V·A Fluorescent Lamp Shunt Capacitive 1200 V·A Fluorescent Lamp Inductive 3600 V·A Halogen Lamp 3600 W
Minimum Switching Time	0.02 second [unit of time]
Time Range	0.5 – 20 min. Stepless Long 60 min. time range available
Impulse Duration	10 second [unit of time]
Appareil	Électronique
Type de charge	2300W Inductive load, cosj = 0.6/230 VAC
Switch Type	SteadyLight
Matériau du boîtier	Heat resistant, self-extinguishing thermoplast
Options Provided	With Switch-Off Warning
Section de câble	Terminal 4 mm ² Terminal 13 mm ²
Connection Mode and Capacity	3 or 4 conductor operated automatically
Control Supply Voltage	230 AC V
Contact Material	silver-tin-oxide (AgSnO ₂)
Rated Switching Capacity	16 A 230 V AC
Switch Off Warning Type	Flickering

Environnement

Température extérieure	–25 ... 50 °C
Statut RoHS	Following EU Directive 2011/65/EU
Informations RoHS	2CDK440004K0202
REACH Declaration	9AKK107492A1907
Informations environnementales	2CDU400020D0201
SCIP	8ec0dc57-a0c8-45f0-a754-21f73a3976d7 Germany (DE)

Dimensions

Produit Largeur Net	17.5 mm
Produit Hauteur Net	90 mm
Produit Longueur Net	58 mm
Poids net	0.08 kg

Commande

Quantité minimum	1 pièce
------------------	---------

Emballage Niveau 1	box 10 pièce
Unités	
Emballage Niveau 1 Poids	1.005 kg
Code douanier	85364900
Pays d'origine	Germany (DE)

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CDK440040D0201
EAC Certificate	9AKK108466A2730
VDE Certificate	9AKK108466A2521

Classifications

ETIM 8	EC000297 - Staircase lighting timer
ETIM 9	EC000297 - Staircase lighting timer
Arborescence du catalogue EPLAN	Electrical engineering / Sensor, switch, and pushbutton / Switch , pushbutton
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 49 00
eClass	V11.0 : 27142307

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Control and Automation Devices → Staircase Switches

