De Dietrich

Induction hob





Product highlights

Perfect Sensor Perfect Sensor: thanks to its connected probe, the hob indicates in real time and to the nearest degree the temperature measured in your dish.

Ref.: DPI7570XT

Perfect Sensor functions The Perfect Sensor hob offers a Chef Mode to program a temperature setpoint and 5 cooking functions to melt, cook under vacuum, reheat, simmer and boil.

Accuracy When time is short, feature and precision are required! Boil, 4 direct accesses, Timers, Boost... are functions to program cooking with efficiency.

GENERAL	
Brand	DE DIETRICH
Commercial code	DPI7570XT
Ean code	3660767975903
Customs code	85166050

FEATURES	
Construction type	Built-in
Hob type	Induction
Top material	Glass ceramic
Width (cm)	65
Energy type	Electric
Top colour	Black
Finishing	R2 rounded edges;Brushed stainless steel finish on connection strip
Number of zones	3
Flexible zone	
Control type	Touch-sensitive buttons
Electronic type	De Dietrich

CONNECTIVITY		
Connectivity	-	
Connectivity type		
Features		
Culinary guide functions		

	Foyer 1	Foyer 2	Foyer 3	Foyer 4	Foyer 5	Foyer 6
Position of the heating element	Front Left	Rear left	Center-right			
Type of heating element	Induction	Induction	Induction			
Dimensions of the heating element (mm)	160	230	280			
Max. power of the heating element in W	2400	3700	3700			
Number of position(s) / cooking zone	20	20	20			
Direct access	<fr found="" not="" value=""></fr>	<fr found="" not="" value=""></fr>	<fr found="" not="" value=""></fr>			
Booster	1	1	1			
Timer	Electronic 99 min	Electronic 99 min	Electronic 99 min			
Electrical energy consumption per zone (EC) Wh/kg	175,1	170,2	168,3			

De Dietrich

Induction hob

FUNCTIONS AND ACCESSORIES	
Functions of the zones	Automatic pan recognition
Probe (with holder)	Yes
Probe functions	Melt;Heat up;Vacuum;Boil;Expert mode
Accessories supplied	
Optional accessories	

SAFETY	
Safety devices	Pack 10 securities
Power indicator	Yes

Ref.: DPI7570XT

INSTALLATION	
Hob maximum electric power input (kW)	7.4
Fuse (A)	32
Voltage (V)	220-240
Frequency (Hz)	50/60
Three-Phase connection	
Total electrical energy consumption (EC)	171,2
Standby consumption (W)	< 0.5
Dimensions of the unboxed product HxWxD (mm)	60X650X515
Dimensions of the packed product HxWxD (mm)	140X750X600
Built-in dimensions HxWxD (mm)	560X490
Length of power supply cord (mm)	130
Plug type	Without
Net weight (kg)	11.00
Gross weight (kg)	11.7

MANUFACTURING	
Country of origin	France
Availability of spare parts (years)	20
Repair index	