

PRODUCT-DETAILS

ST/U10.1.1-825

ST/U10.1.1-825 SmartTouch 10 B/stainless



Informations générales

Extension du type de produit	ST/U10.1.1-825
Code de produit	2TMA310051B0001
EAN	6955891819443
Description courte	ST/U10.1.1-825 SmartTouch 10 B/stainless

Description longue	Freely programmable Touch panel featuring a 10-inch IPS screen with 1280*800 resolution that combines smart home automation and door communication in one device for residential applications, hotels, and commercial buildings. SmartTouch 10 offers home control and monitoring of the free@home, or KNX system and the fully integrated functions of ABB Welcome®. Control, observe and manage your entire installation on one device: Switching - Dimming - Slider - Blind - RGBW control element - Step switch - Scene switch - Display element - Audio control element. With scene function, logic functions, presence simulation and time programs. SmartTouch® 10" can also be used as an end device for communication with the ABB-Welcome outdoor stations, and as part of the ABB-Welcome door communication system. Functions KNX: • A total of 450 control elements are displayed on a maximum of 25 pages. • 80 fault and alarm messages • 30 logic functions • 40 timers • presence simulation for 20 participants • 10 scene actuators • 3 object RTC • Equipped with a hearing loop for coupling the audio signal into hearing aids • Page display with a maximum of 18 touch surfaces on one page free@home: • Twisted pair connection provides a single page with a maximum of 18 controls. • Alternatively, for additional control, connection via wi-fi delivers the same amount of control and features as the free@home App. Welcome: • Integrated IP Gateway • Possibility to integrate ONVIF IP cameras External power supply: 20-32 VDC (SELV) or via the ABB-Welcome system controller. Display size: 25,4cm (10"): Display resolution: 1280*800 : Display screen: IPS display Dimensions (L x W x D): (180.2mm x 254.6mm x 17.5mm) Flush or wall mounted, mount for desktop installation The flat design slim real metal frame sits almost flush with the wall (14mm) and is available in 4 colours (stainless steel, anthracite, gold and rose gold) and black or white glass.
--------------------	---

Commande

EAN	6955891819443
Code douanier	85177900
Quantité minimum	1 pièce
E-Number (Switzerland)	305510185
E-Number (Finland)	2818968

Dimensions

Produit Longueur Net	254.6 mm
Produit Hauteur Net	17.5 mm
Produit Largeur Net	180.2 mm
Poids net	793 g

Emballage

Emballage Niveau 1 Unités	carton 1 pièce
Emballage Niveau 1 EAN	6955891819443
Emballage Niveau 1 Longueur	292 mm

Emballage Niveau 1 Hauteur	37 mm
Emballage Niveau 1 Largeur	239 mm
Emballage Niveau 1 Poids	1.01 kg

Technique

Température de l'air ambiant	Operation 0 ... +45 °C
Compatible Bus Systems	free@home free@home wireless KNX (TP) KNX Welcome
Indice de protection	IP20
Type d'affichage	TFT Touch Display
Type de montage	Flush-mounted (plaster)
Taille d'écran	10 in

Certificats et Déclarations (Numéro de document)

Fiche produit, informations techniques	2CKA001373B5351
Déclaration de Conformité - CE	2CKA100000E4595
Instructions et manuels	2CKA001473B5343
Instructions et manuels (Partie 2)	2CKA001373B5343
REACH Declaration	2TMD081215X2204
Informations RoHS	2CKA200000E7716

Environnement

Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Classifications

ETIM 7	EC000783 - Signalling and operation panel for bus system
ETIM 8	EC000783 - Signalling and operation panel for bus system
eClass	V11.0 : 27143101
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)

Catégories

Produits basse tension → Home and Building Automation → free@home → Visualisation, Display and Signalling → Touch Panels
 Produits basse tension → Home and Building Automation → KNX → Visualisation, Display and Signalling → Touch Panels
 Produits basse tension → Home and Building Automation → Portiers vidéo → Welcome → Video Indoor Stations

