



**Pushing Performance**  
Since 1945

## Han 6B-SCP-HTE-HC-f. SL-M25



Part number	19 30 906 0446
Specification	Han 6B-SCP-HTE-HC-f. SL-M25
HARTING eCatalogue	<a href="https://b2b.harting.com/19309060446">https://b2b.harting.com/19309060446</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> B
Type of hood/housing	Hood
Description of hood/housing	Corrosion resistant
Type	High construction

### Version

Size	6 B
Version	Top entry
Cable entry	1x M25
Locking type	Single locking lever
Field of application	Standard hoods/housings for industrial connectors

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
	IP66
	IP67
Type rating acc. to UL 50 / UL 50E	4
	4X
	12

### Material properties

Material (hood/housing)	Aluminium die-cast
-------------------------	--------------------



**Pushing Performance**  
Since 1945

**Material properties**

Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)

**Specifications and approvals**

Approvals	DNV GL
CE	Yes

**Commercial data**

Packaging size	1
Net weight	137 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140164307
eCl@ss	27440202 Shell for industrial connectors