

Specifications

Livré sans patère



Eaton LUM16025RS

Eaton Emergency Lighting Self-Contained Ultraled 45 refurbished without baseplate.SATI;LED; 45lm, 1h, IP43, IK08

General specifications

PRODUCT NAME	Eaton refurbished emergency luminaire
CATALOG NUMBER	LUM16025RS
EAN	3660191816674
PRODUCT LENGTH/DEPTH	214 mm
PRODUCT HEIGHT	40 mm
PRODUCT WIDTH	105 mm
PRODUCT WEIGHT	0.326 kg
CERTIFICATIONS	NF AEAS
GLOBAL CATALOG	LUM16025RS
PRODUCT TYPE	Refurbished emergency luminaire



Powering Business Worldwide

Product specifications

BATTERY VOLTAGE	3.6 V
BATTERY QUALITY	NiCd
GLOW WIRE TEST	850 °C
PERMISSIBLE AMBIENT TEMPERATURE - MIN	25 °C
PERMISSIBLE AMBIENT TEMPERATURE - MAX	25 °C
PROTECTION CLASS	II
OUTDOOR USE COMPLIANCE	False
EXPLOSION PROTECTED	False
DEGREE OF PROTECTION	IP43
MODE	Maintained (M)
LAMP TYPE	LED not exchangeable
WITH LIGHT SOURCE	True
LAMP HOLDER	None
TYPE OF INDICATOR	Only single-sided
MONITORING EQUIPMENT	Automatic self test
POWER SUPPLY SYSTEM	Peripheral (individual battery)
VOLTAGE TYPE	AC
APPARENT POWER AT MAINS OPERATION	2 VA
POWER FACTOR	0.61
WIRING SYSTEM	Continuous circuit/emergency circuit
WITH REMOTE SWITCH CONNECTION	True
RESERVE-POLARITY PROTECTED	True
CONDUCTOR CROSS SECTION	2.5
CONNECTION TYPE	Plug-in connection
MAX. SYSTEM POWER	1.2 W
RATED LIFE TIME L80/B10 AT 25 °C	51000 hour
TYPE OF CONTROL GEAR	Not required
NOMINAL VOLTAGE AC - MAX	230 V
NOMINAL VOLTAGE AC - MIN	230 V
RATED AMBIENT TEMP ACC. IEC62722-2-1 - MIN	5 °C
RATED AMBIENT TEMP	40 °C

Resources

ACC. IEC62722-2-1 - MAX	
NOMINAL OPERATION TIME - MIN	1 hour
NOMINAL OPERATION TIME - MAX	1 hour
AUTONOMY	1h
MOUNTING METHOD	Wall surface mounted
MATERIAL HOUSING	Plastic
COLOR HOUSING	White
MATERIAL COVER	Plastic, transparent
LABELLING TYPE	Insert sheet/plate
PICTOGRAM INCLUDED	True
NUMBER OF POLES (NUMERIC)	2
IMPACT STRENGTH	IK08
KIND OF LUMINAIRE	Exit sign luminaire
RATED LUMINOUS FLUX ACC. IEC 62722-2-1	45 lm
COLOR TEMPERATURE - MAX	5000 K
COLOR TEMPERATURE - MIN	5000 K
LIGHT DISTRIBUTOR	Reflector
ENERGY EFFICIENCY CLASS OF THE BUILT-IN LAMP	A++, A+, A (LED)
FUNCTION	Escape route signage
COLOR RENDERING INDEX (CRI)	80
LUMINOUS FLUX IN STANDBY MODE	3 lm
NUMBER OF LIGHTING HEADS	1
SUITABLE FOR NUMBER OF LAMPS	2
VIEWING DISTANCE	20 m
FREQUENCY	50Hz
PRODUCT BRANDING	Eaton
NUMBER OF LEDS	2
SHAPE	Rectangular
APPLICATION	Other
TESTING SYSTEM	SATI

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

