




221101E

COPPER LUGS SHORT BARREL A-M & A-L SERIES



GENERAL INFORMATION



UL listed per 486A - 486B up to 35 kV (File nr. E125401).

- The lugs are for use with Cu wire.
- The lugs are manufactured from electrolytic copper tube, annealed to guarantee optimum ductility and electrolytically tin plated to avoid oxidation.
- The tongue is clearly marked with wire size and stud hole dimension.

INSTALLATION INSTRUCTIONS

- 1) Select proper lug for the Cu wire size used.
- 2) Strip the cable insulation for the length indicated.
- 3) Insert conductor into the barrel.
- 4) Select the proper die as indicated in the table.
- 5) Apply the proper # of crimps, as indicated in the same table.



www.cembre.com



CEMBRE S.p.A.
via Serenissima, 9
25135 Brescia
Italy
Ph +39 030 36921
ufficio.vendite@cembre.com
sales@cembre.com

CEMBRE Ltd.
Dunton Park,
Kingsbury Road,
Curdworth, Sutton Coldfield
West Midlands, B76 9EB
United Kingdom
Ph +44 01675 470440
sales@cembre.co.uk

CEMBRE S.a.r.l.
22 Avenue Ferdinand
de Lesseps
91420 Morangis Cedex
France
Ph +33 01 60 49 11 90
info@cembre.fr

CEMBRE España S.L.U.
Calle Verano 6 y 8
Pl Las Monjas
28850 Torrejón de Ardoz
Madrid - Spain
Ph +34 91 4852580
comercial@cembre.com

CEMBRE GmbH
Geschäftsbereich
Energie- und Bahntechnik
Heidemannstr. 166
80939 München
Germany
Ph + 49 89-3580676
info@cembre.de

CEMBRE GmbH
Geschäftsbereich
Industrie und Handel
Boschstraße 7
71384 Weinstadt
Germany
Ph +49 7151-20536-0
info-w@cembre.de

CEMBRE Inc.
Raritan Center Business Park
300 Columbus Circle-S.F.,
Edison, NJ 08837 USA
Ph +1 (732) 225-7415
sales.us@cembre.com
Midwest Office
1051 Perimeter Dr #610
Schaumburg, IL 60173

SIZES	CONDUCTOR RANGE			STRIP LENGTH 	INSTALLATION TOOLING (# of crimps)				
					60 kN (●)	130 kN (◆)		230 kN	520 kN
LUGS	AWG MCM	low str	fine str		DIE SET	NEST + INDENTOR	DIE SET	ECW-H3D	RHU520
		mm²						DIE SET	DIE SET
A1	12-10 AWG	4 - 6		9	ME1-50 (1)	-	-	AU230-130D ADAPTER + 130 kN dies	AU520-130C ADAPTER + 130 kN dies
A2	8 AWG	10		9	ME2-50 (1)	MA2-C+PA10-C (1)	ME2-C (1)		
A3	6 AWG	16		13	ME3-50 (1)	MA3-C+PA10-C (1)	ME3-C (1)		
A5	4 AWG	25		12	ME5-50 (1)	MA5-C+PA10-C (1)	ME5-C (1)		
A7	2 AWG	35	25-35	14	ME7-50 (1)	MA7-C+PA10-C (1)	ME7-C (1)		
A10	2-1/0 AWG	50	35-50	18	ME10-50 (2)	MA10-C+PA10-C (1)	ME10-C (1)		
A14	1/0-2/0 AWG	70	50-70	19	ME14-50 (2)	MA14-C+PA24-C (1)	ME14-C (1)		
A19	2/0-3/0 AWG	95	70-95	24	ME19-50 (2)	MA19-C+PA24-C (1)	ME19-C (1)		
A24	3/0-250 AWG	120	95-120	25	ME24-50 (2)	MA24-C+PA24-C (1)	ME24-C (1)		
A30	250-300 MCM	150	120-150	28	ME30-50 (3)	MA30-C+PA48-C (1)	ME30-C (1)		
A37	300-350 MCM	185	150-185	30	ME37-50 (3)	MA37-C+PA48-C (1)	ME37-C (1)		
A48	350-500 MCM	240	185-240	37	ME48-50 (3)	MA48-C+PA48-C (1)	ME48-C (2)		
A60	500-600 MCM	300	240-300	41	-	MA60-C+PA60-C (1)	ME60-C (3)		
A80	600-800 MCM	400	300-400	43	-	-	ME80-C (3)	ME80-3D (2)	ME80-520 (2)
A100	800-1000 MCM	500	400-500	46	-	-	-	ME100-3D (2)	ME100-520 (2)

- HT51 also with suffix L, D, -KV, L-KV; RH50; RHM50; HT61; B600; RH61; B51, B500, B500ND also with suffixes L, -KV, ■, L ■, L ■-KV; B600C; RH60C
 - ◆ HT120 also with suffix -KV; HT131-C also with suffixes U, LN; RHC131 also with suffixes LN, -KV; RHM132; RHU131-C; B135-C, B131-C also with suffixes U, LN, -KV, ■, LN ■, LN ■-KV; B1350-C, B1300-C also with suffixes U, L, -KV, ■, L ■, L ■-KV; B1320
- Note: Symbol ■ in the tool descriptions could be A, E, J or T suffix; it can be added for commercial purposes only.