

# **Product Highlights**

#### **High-Speed Networking**

Gigabit ports allow you to connect up to eight devices for fast file transfers and smooth media streaming

#### **Automatically Energy Saving**

Energy Efficient Ethernet compliance reduces energy consumption without sacrificing performance while cutting down on your power bill

#### **Eco-Friendly and Economical**

Economical yet innovative design runs cool and quiet, making for an unobtrusive addition to the workplace



# DGS-1008D 8-Port Gigabit Desktop Switch

### **Features**

#### Connectivity

- Eight Gigabit Ethernet LAN ports for high-speed
   wired connections
- Cable Diagnostics Function notifies users of cable conditions through product LEDs

#### **Green Ethernet Features**

- Reduces power to a port when no link is detected
- Adjust power to a port by detecting the length of the connected Ethernet cable

The DGS-1008D 8-Port Gigabit Desktop Switch is part of D-Link's series of SOHO devices that allows you to easily expand and upgrade your network. D-Link's Green Technology provides energy savings, reduces heat, and a longer product life without sacrificing performance or functionality. DGS-1008D provides five Gigabit ports for easy expansion of your network and a quick way to upgrade your network to Gigabit connectivity. An energy-efficient power adapter (EnergyStar Level V qualified), minimised use of harmful substances (RoHS compliant), and recyclable packaging make this switch truly environmentally friendly.

### Fast and Reliable Networking

The D-Link DGS-1008D 8-Port Gigabit Desktop Switch creates a blazing fast network for your office, as its Gigabit Ethernet ports provide high-speed wired connections for up to five PCs or other devices. The DGS-1008D also features QoS, which prioritises network traffic so that time-sensitive data is delivered efficiently, even during bursts of high data traffic. It's stylish, easy-to-use, and comes IPv6-ready for a reliable network today and tomorrow.

## **Conserve Energy**

The 8-Port Gigabit Desktop Switch helps you conserve energy automatically through several methods. It automatically powers down ports that have no link, allowing the switch to save a substantial amount of power by cutting power usage for unused ports or ports connected to computers that have been shut down.

# DGS-1008D 8-Port Gigabit Desktop Switch

Technical Specifications			
General			
Device Interfaces	• Eight 10/100/1000 Gigabit LAN ports		
Functionality			
Advanced Features	<ul> <li>Green Ethernet</li> <li>10 Gbps switching fabric</li> <li>Auto MDI/MDIX crossover for all ports</li> <li>Secure store-and-forward switching scheme</li> </ul>	<ul> <li>Full/half-duplex for Ethernet/Fast Ethernet speeds</li> <li>IEEE 802.3x Flow Control</li> <li>Supports 9,216 Byte Jumbo Frames</li> <li>Supports IEEE 802.1p QoS (4 Queues, Strict Mode)</li> <li>Supports Cable Diagnostics Function</li> </ul>	
Standards	<ul> <li>IEEE 802.3 10BASE-T Ethernet</li> <li>IEEE 802.3u 100BASE-TX Fast Ethernet</li> <li>IEEE 802.3ab 1000BASE-T Gigabit Ethernet</li> </ul>	<ul> <li>ANSI/IEEE 802.3 NWay auto-negotiation</li> <li>IEEE 802.3x Flow Control</li> <li>IEEE 802.3az Energy-Efficient Ethernet (EEE)</li> </ul>	
Protocol	• CSMA/CD		
Data Transfer Rates	<ul> <li>Ethernet:</li> <li>10 Mbps (half duplex)</li> <li>20 Mbps (full duplex)</li> </ul>	<ul> <li>Fast Ethernet:</li> <li>100 Mbps (half duplex)</li> <li>200 Mbps (full duplex)</li> <li>Gigabit Ethernet:</li> <li>2000 Mbps (full duplex)</li> </ul>	
Transmission Method	Store-and-forward		
MAC Address Table	• 4 K		
MAC Address Learning	Automatic Update		
Packet Filtering/Forwarding Rates	<ul> <li>Ethernet: 14,880 pps per port</li> <li>Fast Ethernet: 148,800 pps per port</li> </ul>	• Gigabit Ethernet: 1,488,000 pps per port	
RAM Buffer	• 128 KB per device		
Physical			
LED Indicators	• Per port: Link/Activity	Per device: Power	
Media Interface Exchange	Auto MDI/MDIX adjustment for all ports		
Dimensions	• 138 x 85 x 34 mm		
Weight	• 400 grams		
Power	• 5 V/1 A Power Adapter		
Power Consumption	• Maximum: 2.55 W	• Standby: 0.4 W	
Temperature	• Operating: 0 to 40 °C (32 to 104 °F)	• Storage: -10 to 70 °C (14 to 158 °F)	
Humidity	Operating: 10% to 90% non-condensing	Storage: 5% to 90% non-condensing	
MTBF	• 1,046,472 hours		
Certifications	• CE class B, FCC class B, ICES-003 Class B, VCCI class B	CE class B, FCC class B, ICES-003 Class B, VCCI class B, C-Tick, cUL, CB, LVD	



#### For more information: www.dlink.com

D-Link European Headquarters. D-Link (Europe) Ltd., First Floor, Artemis Building, Odyssey Business Park, West End Road, South Ruislip HA4 6QE, United Kingdom. Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2020 D-Link Corporation. All rights reserved. E&OE.

