


## KSA1000DLF4B

Canalis - elbow for trunking - 1000 A - made to measure - downward mounting



### Main

Range of product	Canalis
Product name	KS
Product or component type	Elbow
Busbar description	Standard
Material	Aluminium
Device application	Change direction
[Ie] rated operational current	800 A 35 °C 1000 A 35 °C
Direction change type	Direction 1 : flat to downward - neutral to left

### Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
Operating angle	90...180 °
Mounting location	On trunking
Electrical connection	Lubricated sliding contact
Mounting mode	By screws
Standards	IEC 60439-2 IEC 61439-6
Width	146 mm
Depth	111 mm
Height	290...785 mm
Colour	White : RAL 9001
Product weight	14.4 kg

### Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

### Offer Sustainability

Sustainable offer status	3606480003608
RoHS (date code: YYWW)	Compliant - since 1012
REACH	Reference not containing SVHC above the threshold
Product environmental profile	3606480003608

### Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.