



Main

| | |
|--------------------------------|---|
| Range of product | Canalis |
| Product name | KS |
| Product or component type | Multiple elbow |
| Busbar description | Standard |
| Device application | Change direction |
| [Ie] rated operational current | 800 A at 35 °C 1000 A at 35 °C |
| Direction change type | Direction 3: flat to right - neutral to left Direction 1: edgewise to upward - neutral to down |

Complementary

| | |
|--------------------------------|--|
| [Ue] rated operational voltage | 230...690 V |
| Network frequency | 50/60 Hz |
| Dimension type | Made to measure |
| Operating angle | 90 ° |
| Length | Direction 1 : 290...785 mm Direction 3 : 290...785 mm |
| Height | Direction 2 : 200...575 mm neutral down in the current direction with top view |
| Mounting support | Busbar |
| Mounting mode | By screws |
| Electrical connection | Lubricated sliding contact |
| Standards | IEC 60439-2 IEC 61439-6 |
| Width | 147 mm |
| Colour | White: RAL 9001 |
| Product weight | 14.4 kg |

Environment

| | |
|-------------------------|------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to IEC 62262 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1012 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|