# « Manual » M3-M

## M3-M : Portable model with handle

- Very portable thanks to its handle (height=11cm) and its light weight (1.25kg), this measuring device will allow you to measure your cables, ropes, pipes...
- Up to Ø22mm.
- Counter in dm measures up to 9999.9 meters
- Measuring wheel width 25 mm
- Development 200 mm
- In ribbed metal
- Manual use
- Dimensions and weight (M3-M): I130 x W 250 x H 200 mm (including handle 11 cm) - 1.25 kg

#### Code E3350010

Measuring a long product by unreeling it cannot be absolutely precise on principle. The user is to perform their own tests to determine the accuracy percentage for the various products to be measured.

## M3

#### Diameter 1 to 22 mm

- Counter in dm measures up to 9999.9 meters
- Measuring wheel width 25 mm Development 200 mm in ribbed metal
- Dimensions and weight (M3-T): I 130 x W 250 x H 140 mm - 1,9 kg

Measuring a long product by unreeling it cannot be absolutely precise on principle. The user is to perform their own tests to determine the accuracy percentage for the various products to be measured.

## M35

#### Diameter 1 to 35 mm

- Counter in cm measures up to 9,999.95 meters
- Measuring wheel: width: 35 mm, development: 500 mm, made of ribbed metal or synthetic ribbed metal (for metal cables)
- Resistant aluminium ends
- Very stable base (17 kg), which can be adjusted at 3 heights (650, 740 or 820 mm)
- Dimensions and weight (M35-T) : I 160 x W 300 x H 160 mm - 4,1 kg

	Versions	Usage	metal wheel	synthetic wheel
	M35-T	table model	E3350354	E3350355
	M35-P	freestanding model	E3350353	E3350356
	M35-B	for PKCO	E3350351	E3350358
	M35-C	for ST1-ST2	E3350352	E3350359
	M35-D	for BOBI	E3350369	E3350379

Measuring a long product by unreeling it cannot be absolutely precise on principle. The user is to perform their own tests to determine the accuracy percentage for the various products to be measured.

# M50

## Diameter 1 to 50 mm


- Counter in cm measures up to 9,999.95 meters.
- Measuring real 50mm in length, 500m development, made synthetically or from polyurethane (for heavy use).
- Guiding at inlet and outlet by means of steel rollers and under the measuring wheel by means of a flanged tensioner
- Tabletop model and free standing model (identical to that of the M35).
- Manual usage or on a winding machine
- Dimensions and weight ((M50-T) - I 195 x P 380 x H 175 mm - 8.7 kg

Measuring a long product by unreeling it cannot be absolutely precise on principle. The user is to perform their own tests to determine the accuracy percentage for the various products to be measured.

www.cable-equipements.com 📉

Versions	Usage	Code
M3-T	table model	E3350004
M3-B	for PKCO	E3350002
M3-C	for ST1-ST2	E3350001
M3-D	for BOBI	E3350009

Code with







Versions	Usage	Code with polyu- rethane wheel
M50-T	table model	E3350520
M50-P freestanding mo- del		E3350521



	1
u- I	Docum