

# MATERIAL SAFETY DATA SHEET (MSDS)

- Section 1 Product And Manufacturer
- Section 2 Hazardous Components
- Section 3 Physical Data
- Section 4 Protection
- Section 5 First Aid Measures
- Section 6 Flammability Data
- Section 7 Reactivity Data
- Section 8 Control Measures
- Section 9 Health Hazard Data
- Section 10 Sulfuric Acid Precautions
- Section 11 Transportation Regulations
- Section 12 Ecological Information
- Section 13 Disposal Considerations
- Section 14 Transport Information



## **FUJIAN MINHUA POWER SOURCE CO., LTD**

19/F., Be-Top Plaza, Wuyuanwan BCD, Xiamen, Fujian, P. R. China

Tel: +86-592-3300610 (20 lines) Fax: +86-592-3300573

Website: [www.mhb-battery.com](http://www.mhb-battery.com) Email: [sales@mhb-battery.com](mailto:sales@mhb-battery.com)

**SECTION 1--- PRODUCT AND MANUFACTURER**

**Product Name:** Sealed Maintenance Free battery

**Manufacturer:**

**FUJIAN MINHUA POWER SOURCE CO., LTD**

19/F., Be-Top Plaza, Wuyuanwan BCD, Xiamen, Fujian, P. R. China

Tel: +86-592-3300610 (20 lines) Fax: +86-592-3300573

Website: www.mhb-battery.com Email: sales@mhb-battery.com

**SECTION 2--- HAZARDOUS COMPONENTS**

Components	%Wt.	TLV	LD50 Oral	LC50 Inhalation	LC50 Contact	CAS NO.
Lead (Pb, PbO <sub>2</sub> , PbSO <sub>4</sub> )	About 70%	0.050mg/m <sup>3</sup>	Š,(500) mg/Kg	N/A	N/A	7439-92-1
Sulfuric Acid	About 20%	1 mg/m <sup>3</sup>	(2.14) mg/Kg	N/A	N/A	7664-93-9
Fiberglass Separator	About 5%	N/A	N/A	N/A	N/A	65997-17-3
Container (ABS or PP)	About 5%	N/A	N/A	N/A	N/A	25155-30-0

**SECTION 3--- PHYSICAL DATA**

Components	Density	Melting Point	Solubility (in H <sub>2</sub> O)	Odor	Appearance
Lead	11.35	327.4°C	None	None	Silver-Gray Metal
Lead Sulfate	6.25	1170°C	40 mg/l (15°C)	None	White Powder
Lead Dioxide	9.4	290°C	None	None	Brown Powder
Sulfuric Acid	About 1.31(25°C)	About 114°C (Boiling)	100%	Acidic	Clear Colorless Liquid
Fiberglass Separator	N/A	N/A	Slight	Toxic	White Fibrous Glass Membrane
Container (ABS or PP)	N/A	N/A	NONE	No Odor	Solid Plastics

**SECTION 4---PROTECTION**

Exposure	Protection	Comments

Skin	Rubber gloves, Apron, Safety shoes	Protective equipment must be worn if battery is cracked or otherwise damaged.
Respiratory	Respirator (for lead)	A respirator should be worn during reclaim operations if the TLV exceeded.
Eyes	Safety goggles, Face Shield	In the UK use of this material must be assessed under the COSHH regulations.

#### SECTION 5--- FIRST AID MEASURES

Emergency and First Aid Procedures	Contact with internal components if battery is opened/broken.
1. Inhalation	Remove to fresh air and provide medical oxygen/CPR if needed. Obtain medical attention.
2. Eyes	Immediately flush with water for at least 15 minutes, hold eyelids open. Obtain medical attention.
3. Skin	Flush contacted area with large amounts of water for at least 15 minutes. Remove contaminated clothing and obtain medical attention if necessary.
4. Ingestion	Do not induce vomiting. If conscious drink large amounts of water/milk. Obtain medical attention. Never give anything by mouth to an unconscious person

#### SECTION 6--- FLAMMABILITY DATA

Components	Flash Point	Explosive Limits	Comments
Lead	None	None	
Sulfuric Acid	None	None	
Hydrogen	259°C	4%-74.2%	Emit hydrogen only if over charged (Voltage>2.4 VPC). To avoid the chance of a fire or explosion, keep sparks and other sources of ignition away from the battery. Extinguishing Media: Dry chemical, Foam, CO2
Fiberglass Separator	N/A	N/A	Toxic vapors may be released. In case of fire: wear self-contained breathing apparatus.
ABS	None	N/A	Danger: Vapors may cause Flash Fire. Harmful or Fatal if Swallowed. Vapor Harmful.
PP	None	N/A	Temperatures over 300 °C (572°F) may release combustible gases. In case of fire: wear positive pressure self-contained breathing apparatus.

#### SECTION 7--- REACTIVITY DATA

Components	Lead/lead compounds
Stability	Stable
Incompatibility	Potassium, carbides, sulfides, peroxides, phosphorus, sulfurs
Decomposition Products	Oxides of lead and sulfur.
Condition To Avoid	High temperature, Sparks and other sources of ignition.

Components	Sulfuric Acid
Stability	Stable at all temperatures
Polymerization	Will not polymerize
Incompatibility	Reactive metals, strong bases, most organic compounds
Decomposition Products	Sulfuric dioxide, trioxide, hydrogen sulfide, hydrogen
CONDITIONS TO AVOID	Prohibit smoking, sparks, etc. from battery charging area. Avoid mixing acid with other chemicals.

### SECTION 8---CONTROL MEASURES

1. Store lead/acid batteries with adequate ventilation. Room ventilation is required for batteries utilized for standby power generation. Never recharge batteries in an unventilated, enclosed space.
2. Do not remove vent caps. Follow shipping and handling instructions that are applicable to the battery type. To avoid damage to terminals and seals, do not double-stack industrial batteries.

### STEPS TO TAKE IN CASE OF LEAKS OR SPILLS

If sulfuric acid is spilled from a battery, neutralize the acid with sodium bicarbonate (baking soda), sodium carbon (soda ash), or calcium oxide (lime).

Flush the area with water discard to the sewage systems. Do not allow unneutralized acid into the sewage system.

### WASTE DISPOSAL METHOD:

Neutralized acid may be flushed down the sewer. Spent batteries must be treated as hazardous waste and disposed of according to local state, and federal regulations. A copy of this material safety data must be supplied to any scrap dealer or secondary smelter with battery.

### ELECTRICAL SAFETY

Due to the battery's low internal resistance and high power density. High levels of short circuit can be developed across the battery terminals. Do not rest tools or cables on the battery. Use insulated tools only.

Follow all installation instruction and diagrams when installing or maintaining battery systems.

### SECTION 9---HEALTH HAZARD DATA

**LEAD:** The toxic effects of lead are accumulative and slow to appear. It affects the kidneys, reproductive, and central nervous system.

The symptoms of lead overexposure are anemia, vomiting, headache, stomach pain (lead colic), dizziness, loss of appetite, and muscle and joint pain. Exposure to lead from a battery most often occurs during lead reclaim operations through the breathing or ingestion of lead dusts and fumes.

**THIS DATA MUST BE PASSED TO ANY SCRAP OR SMELTER WHEN A BATTERY IS RESOLD.**

**SULFURIC ACID:** Sulfuric acid is a strong corrosive. Contact with acid can cause severe burns on the skin and in the eyes. Ingestion of sulfuric acid will cause GI tract burns. Acid can be release if the battery case is damaged or if the vents are tampered with.

**FIBERGLASS SEPARATOR:** Fibrous glass is an irritant of the upper respiratory tract, skin and eyes. For exposure up to 10F/CC use MSA Comfort with type H filter. Above 10F/CC up to 50F/CC use Ultra-Twin with type H filter. NTP or OSHA does not consider this product carcinogenic.

#### **SECTION10--- SULFURIC ACID PRECAUTIONS**

**Stability:** Stable Substances to be avoided include water, most common metals, organic materials, strong reducing agents, combustible materials, and bases, oxidizing agents. Reacts violently with water - when diluting concentrated acid, carefully and slowly add acid to water, not the reverse. Reaction with many metals is rapid or violent, and generates hydrogen (flammable, explosion hazard).

**INHALATION:** Acid mist form formation process may cause respiratory irritation, remove from exposure and apply oxygen if breathing is difficult.

**SKIN CONTACT:** Acid may cause irritation, burns or ulceration. Flush with plenty of soap and water, remove contaminated clothing, and see physician if contact area is large or if blisters form.

**EYE CONTACT:** Acid may cause severe irritation, burns, cornea damage and blindness. Call physician immediately and flush with water until physician arrives.

**INGESTION:** Acid may cause irritation of mouth, throat, esophagus and stomach. Call physician. If patient is conscious, flush mouth with water, have the patient drink milk or sodium bicarbonate solution.

**DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON.**

#### **SECTION11---TRANSPORTATION REGULATIONS**

We, FUJIAN MINHUA POWER SOURCE CO., LTD, hereby certify that all MHB Valve Regulated Rechargeable Sealed Lead Acid batteries conform to the UN2800 classification as "Batteries, wet, Non- Spillable, and electric storage" as a result of passing the Vibration and Pressure Differential Test described in DOT [49 CFR 173.159(d) and IATA/ICAO [Special Provision Specia SP48, A67 A167 A183)

MHB Batteries meet the related conditions are EXEMPT from hazardous goods regulations for the purpose of transportation by DOT, and IATA/ICAO, and therefore are unrestricted for transportation by any means. For all modes of transportation, each battery outer package is labeled "NON-SPILLABLE".

#### **SECTION12---Ecological Information**

When promptly used or disposed the battery does not present environmental hazard. When

disposed,keep away from water,rain and snow.

### **SECTION 13----Disposal Considerations**

Appropriate Method of Disposal of Substance or Preparation

Dispose of the batteries in accordance with approved local ,state,and federal requirements

Consult state environmental agency.

### **SECTION 14- Transport Information**

Air Transportation

Proper Shipping Name: Batteries, wet, non-spillable

UN Identification: UN2800

Hazardous Class: 8

Special Provision A48: Packing Test are not considered necessary.

Special provision A67 60 Edition: MHB VRLA batteries meet the requirements of  
Packing Instruction 872.

The battery has been prepared for transport so as to prevent:

- a) A short-circuit of the battery's terminal by packing in a strong and sturdy carton box, and/or
- b) The battery has been fitted with an insulating cover (made from ABS) which prevents contact with the terminals.
- c) Unintentional activation is thus prevented

The words "NOT RESTRICTED" and the special Provision (SP) number must be indicated on all shipping documents

Special Provision A164:

Any electrical battery or battery powered device, equipment or vehicle having the potential of a dangerous of heat must be prepared for transport so as to prevent:

- (a) A short circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals; or in the case of equipment, by disconnection of the battery and protection of exposed terminals); and
- (b) Unintentional activation

Special Provision A183:

Waste batteries and batteries being shipped for recycling or disposal are forbidden from air transport unless approved by the appropriate national authority of the State of Origin and the State of the Operator.

Marine Transportation

Proper Shipping Name: Batteries, wet, non-spillable

UN Identification: UN2800

Hazardous Class: 8

MHB VRLA batteries have been tested and meet the non-spillable criteria listed in CFR 49, 173, 159 (d) C(3) (i) and (ii).

Non-spillable batteries are excepted from CFR 49, Subchapter C requirement, provided that the following criteria are met:

1. The batteries must be protected against short circuits and securely packaged.
2. The batteries and their outer packaging must be plainly and durably marked "NON-SPILLABLE" or "NONS-PILLABLE BATTERY".

Additional Information:

Each battery and the outer packaging must be plainly and durably marked "NON-SPILLABLE" or "NONS-PILLABLE BATTERY".

Transport requires proper packaging and paperwork, including the nature and quantity of goods, per applicable origin/destination/customs points as shipped.

III (302/311/312/313)» (SARA)  
《Resource Conservation and Recovery Act》 (RCRA)  
《Safety Drinking Water Act》 (CWA)  
《California Proposition 65》  
《Code of Federal Regulations》 (CFR)  
In accordance with all Federal, State and Local laws.

**SECTION16---Additional Information**

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose

ISSUE DATE: DEC 26TH,2018

**24-hour telephone service: 0086-592-3300610**

**THIS MSDS IS VALID ON THE DATE FROM THE YEAR OF 2019 TO 2020**