


Product Description:

Appliques murales décoratives LED. Conçue pour fournir un éclairage d'accentuation subtil dans les applications intérieures et extérieures. Disponible avec un diffuseur opale pour l'éclairage général ou des caches demi-lune pour les circulations. La gamme est fabriquée en polycarbonate et est entièrement résistante à la corrosion, idéal pour les applications résidentielles, commerciales et en bord de mer.

Product Image:



Line Drawing



Product Specs:

Technology	LED	Input Voltage	220-240V AC
Lamp Base	Aucun	Positional Adjustment	Fixe
Number of LEDs	70	Lifetime L70 (hrs)	30000
Input Frequency	50/60HZ	Dimmable	Non
Dali	Non	IP Rating	IP65
IK Rating	IK10	Operating Env. Temp. (Min) °C	-10°C
Operating Env. Temp. (Max) °C	40°C	Power Factor	0.9
Length (mm)	140	Width (mm)	140
Weight (Kg)	0.224		

SKU Table and Ordering:

SKU Code	Wattage	Beam Angle	Lumens	Lumens/Watt	CRI	Colour	Finish Colour
EN-WL4/30	4	120	240	60	80	3000	Noir
EN-WL4/40	4	120	300	75	80	4000	Noir

Compliance & Approvals:



Warranty:

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Head Office

Apex Park
6 Little Burrow
Welwyn Garden City AL7 4SW
United Kingdom
Tel : +44 (0) 1707 228 700